TEE INSTALLATION KIT



Note Tee Installation Kits do not have IAPMO or ICC approval. Provides a simple method of breaking into and branching off a rigid run without altering existing pipe work.

TEST CAP

PART NO.	SIZE CTS	BAG QTY	BOX QTY
PSEI4620	1/2"	10	150
PSEI4628	3/4"	5	80
PSEI4636	1"	5	40

Easy to Connect





Easy to Disconnect

The unique feature of the Speedfit concept is the ability to easily connect and disconnect the Test Cap. Test Caps also provide a leak-proof seal.

They can be used to temporarily "cap-off" installations for pressure testing and rough inspections.

With Speedfit Test Caps there is no need for tools, sweating or threading. They can be used with plastic or copper pipe, and are reusable many times over.

FEMALE SWIVEL CONNECTOR

PART NO.	SIZE CTS x NPS	BAG QTY	BOX QTY	
PEISTC2034	1/2" x 1/2"	10	50	

Hand tighten only, no spanner required

FEMALE SWIVEL ELBOW

	PART NO.	SIZE CTS x NPS	BAG QTY	BOX QTY	
	PEIBTC2034	1/2" x 1/2"	10	50	

Hand tighten only, no spanner required

FEMALE BALLCOCK CONNECTOR



Connects to toilet fill valve.

Hand tighten only, no spanner required

FEMALE BALLCOCK ELBOW



Connects to toilet fill valve.

Hand tighten only, no spanner required

Speedfit[®] Secure

This Range of connectors has been developed to supply the user with a secure pipe connection where threaded applications are required. The adapters use a unique locking device which eradicates the possibility of accidental pipe release.

Installation instructions are provided with the product.

MALE CONNECTOR

	PART NO.	SIZE CTS x NPT	BAG QTY	BOX QTY	
ALLE ALLE	PSEI012024	1/2" x 1/2" 1/2" x 3/4"	10 5	80 60	
	PSEI012026 PSEI012826	3/4" x 3/4"	5 5	60 50	
	PSEI013626	1" x 3/4"	2	30	
	PSEI013628	1" x 1"	2	20	

FEMALE CONNECTOR

PART NO.	SIZE CTS x NPSM	BAG QTY	BOX QTY	
PSEI452826	3/4" x 3/4"	5	40	

MALE FIXED ELBOW



PART NO.	SIZE CTS	BAG QTY	BOX QTY	
PSEI482024	1/2" x 1/2"	5	60	

SHUT OFF VALVE NEW



Firm 1/4 turn handle, prevents unwanted movement.