

# TaskWork Linear

## 12 Volt & 24 Volt Xenon



STEP 1  
**EASY-TO-INSTALL TRACK**

- B** 10243 BK, WH (50-pack)  
10283 BK, WH (10-pack)
- Snaps on the score, every 6"
  - Captive screws every 6"
  - White or Black finish
  - 4' linear track

### Accessories

- 10240 BK, WH – Wire End Caps  
10241 BK, WH – Track End Caps  
10298 WH – Double-Sided Tape (1/2" x 15')  
10299 – Box Of Screws (100 pieces)

10240 BK, WH  
Wire End Caps



10241 BK, WH  
Track End Caps

10244 BK, WH  
Splicing Block Connector  
(listed enclosure required)



10254 BK, WH  
Splicing Block with Enclosure



### AVAILABLE FINISHES

Black (BK) and White (WH)



10215 BK  
In-Line Fixture



10215 WH  
In-Line Fixture

STEP 2  
**LOW-VOLTAGE CABLE**

- C** 10230 BK, WH – Linear Cable 25 Feet  
10232 BK, WH – Linear Cable 100 Feet  
10233 BK, WH – Linear Cable 500 Feet  
10234 BK, WH – Linear Cable 1000 Feet

- F** Stabilizer Clip  
10242 BK, WH

- Designed to attach Kichler Linear SPT cable to any wood surface
- Prevents cable from sagging
- Allows for making turns in cable in areas where cable is not supported by track

### Splicing Block Connector

- 10244 BK, WH (listed enclosure required)  
10254 BK, WH - Splicing Block With Enclosure

- Four connections allow up to four rounds of NM or Kichler's SPT cable in any combination
- Possible combinations
  1. NM cable in and up to three SPT cables out
  2. SPT cable in and up to three SPT cables out
  3. NM cable in and up to three NM cables out. All wiring should be in accordance with local and national codes

STEP 3  
**SELECT NUMBER OF IN-LINE OR DIRECTIONAL FIXTURES AND FINISH. FOR IN-LINE, SELECT VOLTAGE & WATTAGE. FOR DIRECTIONAL, SELECT 12° SPOT OR 26° FLOOD & VOLTAGE.**

- A** In-Line Fixture
- 10215 BK, WH – 12 Volt/5 Watt  
10216 BK, WH – 12 Volt/10 Watt  
10217 BK, WH – 24 Volt/5 Watt  
10218 BK, WH – 24 Volt/10 Watt
- Shipped with frosted bulb pre-installed
  - Easy to handle, no sharp edges, no bent reflectors
  - Less than width of track

### In-Line Replacement Lamps

- 10245 – 12 Volt/5 Watt  
10246 – 24 Volt/5 Watt  
10247 – 12 Volt/10 Watt  
10248 – 24 Volt/10 Watt
- Bright Xenon bulb
  - Frosted for no glare
  - 5 or 10 Watt options

- E** Multi-Directional Fixture  
10261 BK, WH

- Order bulbs separately
- G4, MRC-11
- Added versatility for your Linear Lighting
- Highlight architectural features
- Overall dimensions (with bulb) 2-1/4" H x 1-1/2" W x 1-1/2" H
- Maintain clearance of 3" from other surfaces. Space no closer than 3" from other lampholders

### Multi-Directional Lamps

- 10256 CLR – 12 Volt, 12° spot (20 Watt)  
10257 CLR – 12 Volt, 26° flood (20 Watt)  
10258 CLR – 24 Volt, 12° spot (20 Watt)  
10259 CLR – 24 Volt, 26° flood (20 Watt)
- Rated life 2,000 hours

10261 BK, WH  
Multi-Directional Fixture  
with  
10256 CLR  
Multi-Directional Lamp

