



	15843 CO, NBK, TZT - LED DECORATIVE HAMMERED ROOF	15871 BBR, TZT - LED CAST HAMMERED ROOF
Description	Pierced shade sheds decorative patterned light with the added benefit of LED technology. Coordinates with matching LED deck light 15763 on page 23.	Pierced shade sheds decorative patterned LED light over shrubs, gardens, or walkways. Coordinates with matching LED deck light 15763 on page 23.
Ordering Guide & Finish	15843 CO - Unfinished Copper (Marine grade powder coat) 15843 NBK - New Brick™ (Marine grade powder coat) 15843 TZT - Textured Tannery Bronze™ (Marine grade powder coat)	15871 BBR - Bronzed Brass (Marine grade powder coat) 15871 TZT - Textured Tannery Bronze™ (Marine grade powder coat)
Housing	Brass or Copper (copper will naturally patina over time)	Cast Aluminum, Cast Brass
Light Source	3 Integrated High Output Nichia® LEDs, tightly binned for color uniformity, and constant current driver	3 Integrated High Output Nichia® LEDs, tightly binned for color uniformity, and constant current driver
Color Temp. (CCT) & CRI	3000K (-200/+125) / 80s CRI	3000K (-200/+125) / 80s CRI
Power Usage at 12V AC Input VA and Watts	4 W, 5.8 VA, Multiply fixture VA by the number of fixtures used to determine size of transformer	4 W, 5.8 VA Multiply fixture VA by the number of fixtures used to determine size of transformer
Operating Voltage Range	9V-15V AC/DC with no loss in output due to constant current technology	9V-15V AC/DC with no loss in output due to constant current technology
Lumen Maint.	Tested to an L-70 of 40,000 hours	Tested to an L-70 of 40,000 hours
Total Lumens & Efficacy	3000K = 187 Lm 3000K= 47 Lm/W	3000K = 187 Lm 3000K= 47 Lm/W
Wiring	30" of usable #18-2, SPT-1-W leads. Cable connector supplied	30" of useable #18-2, SPT-1W leads. Cable connector supplied
Mounting Acces. Included	8" in-ground stake	8" In-ground stake
Optional Acces.	15601 - Surface Mounting Flange 15607 - Surface Mounting Bracket	15601 - Surface Mounting Flange 15607 - Surface Mounting Bracket
Incandescent	15443 - on page 80	15471 - on page 81
Notes	Subjected to Highly Accelerated Life Testing - 3rd party reliability testing Not for use with electronic transformers	Subjected to Highly Accelerated Life Testing - 3rd party reliability testing Not for use with electronic transformers
Fixture Photometric (fc)	Distance from Light 0' 1' 2' 3' 4' 5' 6' 7' 8' Footcandles 10.9 5.8 2.3 1.0 0.43 0.25 0.13 0.06 0.01	Distance from Light 0' 1' 2' 3' 4' 5' 6' 7' 8' Footcandles 10.9 5.8 2.3 1.0 0.43 0.25 0.13 0.06 0.01