




INCANDESCENT/LED 12V HYBRID IN-GROUND



15194 AZ - ENCLOSED PAR 36 WELL

15190 BK - MR16 MINI WELL

| | | |
|----------------------------------|---|--|
| Description | Completely sealed well light creates unique lighting effects and reduces maintenance with Rock Guard/Glare Shield accessory (15694 AZ) on page 152. | Smaller version of our popular standard well light to shed focused upwards illumination on special features in the landscape. Recommended for salt-air environments. |
| Ordering Guide | 15194 AZ - Architectural Bronze™ | 15190 BK - Black |
| Housing | Durable high temperature polymeric housing material. Glass lens for watertight outdoor inground use. | Durable high heat thermo-plastic composite resin. Heat resistant convex shaped glass lens. Fully sealed for watertight outdoor usage. |
| Lamp Base | 12V PAR 36 lamp  | 12V bi-pin, high temperature porcelain socket  |
| Supplied Lamp | Lamp not supplied unless noted Power usage at 12V AC input VA MAX: 50-W(VA) 50-W(VA) PAR 36 | Lamp not supplied unless noted Power usage at 12V AC input VA MAX: 50-W(VA) 50-W(VA) MR-16: 35-W(VA) Max. MR-11 |
| Incandescent Lamp Options | N/A | N/A |
| LED Lamp Options | 11W PAR36/AR111 (18021-18029) see page 159 Compares to 50W Halogen | 4W (18000-18011) see page 159 Compares to 20W Halogen |
| Wiring | 34" of usable #18-2, SPT-1-W leads. Cable connector supplied. Supply wire with lugs attach directly to PAR 36 light bulb screw terminals | 36" of usable #18-2, SPT-1-W leads. Cable connector supplied |
| Optional Lens Accessories | 15694 - Rock Guard | N/A |
| Notes | See page 200 for photometrics | U.S. Patent No. D437,652 See page 200 for photometrics |

 Denotes fixture is compatible with incandescent or LED lamps.