



15750 TZT - LED VINTAGE PARK™

15763 TZT - LED DECORATIVE HAMMERED ROOF

<b>Description</b>	19 <sup>th</sup> century charm with the energy efficient benefit of LED technology.	Traditional designed pierced shade and scalloped edge combines with the energy efficient benefit of LED technology. Coordinates with matching LED path light 15871 and 15843 on page 10.																																																																
<b>Ordering Guide &amp; Finish</b>	15750 TZT - Textured Tannery Bronze™ (Marine grade powder coat)	15763 TZT - Textured Tannery Bronze™ (Marine grade powder coat)																																																																
<b>Housing</b>	Cast Aluminum	Brass																																																																
<b>Light Source</b>	1 Integrated High Output Nichia® LED, tightly binned for color uniformity, and constant current driver	1 Integrated High Output Nichia® LED, tightly binned for color uniformity, and constant current driver																																																																
<b>Color Temp. (CCT) &amp; CRI</b>	3000K (-200/+125) / 80s CRI	3000K (-200/+125) / 80s CRI																																																																
<b>Power Usage at 12V AC Input VA and Watts</b>	1.9 W, 2.4 VA Multiply fixture VA by the number of fixtures used to determine size of transformer	1.9 W, 2.4 VA Multiply fixture VA by the number of fixtures used to determine size of transformer																																																																
<b>Operating Voltage Range</b>	9V- 15V AC/DC with no loss in output due to constant current technology	9V- 15V AC/DC with no loss in output due to constant current technology																																																																
<b>Lumen Maint.</b>	Tested to an L-70 of 40,000 hours	Tested to an L-70 of 40,000 hours																																																																
<b>Total Lumens &amp; Efficacy</b>	3000K = 50 Lm 3000K= 26 Lm/W	3000K = 50 Lm 3000K= 26 Lm/W																																																																
<b>Wiring</b>	72" of usable #18-2, SPT-1-W leads. Cable connector supplied	72" of usable #18-2, SPT-1-W leads. Cable connector supplied																																																																
<b>Mounting Acces. (Included)</b>	Stainless steel mounting bracket	Stainless steel mounting bracket																																																																
<b>Notes</b>	Subjected to Highly Accelerated Life Testing - 3rd party reliability testing Not for use with electronic transformers	Subjected to Highly Accelerated Life Testing - 3rd party reliability testing Not for use with electronic transformers																																																																
<b>Photometric with Supplied Lamp</b>	<table border="1"> <thead> <tr> <th>Mounting Height</th> <th>0'</th> <th>0.5'</th> <th>1'</th> <th>2'</th> <th>3'</th> <th>4'</th> <th>5'</th> </tr> </thead> <tbody> <tr> <td>6"</td> <td>61.9</td> <td>13.3</td> <td>2.0</td> <td>0.1</td> <td>0.04</td> <td>0.01</td> <td>-</td> </tr> <tr> <td>12"</td> <td>14.7</td> <td>8.4</td> <td>3.3</td> <td>0.5</td> <td>0.1</td> <td>0.03</td> <td>-</td> </tr> <tr> <td>30"</td> <td>2.2</td> <td>2.0</td> <td>1.6</td> <td>0.8</td> <td>0.36</td> <td>0.15</td> <td>-</td> </tr> </tbody> </table>	Mounting Height	0'	0.5'	1'	2'	3'	4'	5'	6"	61.9	13.3	2.0	0.1	0.04	0.01	-	12"	14.7	8.4	3.3	0.5	0.1	0.03	-	30"	2.2	2.0	1.6	0.8	0.36	0.15	-	<table border="1"> <thead> <tr> <th>Mounting Height</th> <th>0'</th> <th>0.5'</th> <th>1'</th> <th>2'</th> <th>3'</th> <th>4'</th> <th>5'</th> </tr> </thead> <tbody> <tr> <td>6"</td> <td>69.4</td> <td>14.4</td> <td>1.8</td> <td>0.08</td> <td>0.03</td> <td>-</td> <td>-</td> </tr> <tr> <td>12"</td> <td>15.3</td> <td>8.6</td> <td>3.4</td> <td>0.37</td> <td>0.08</td> <td>0.02</td> <td>-</td> </tr> <tr> <td>30"</td> <td>2.4</td> <td>2.0</td> <td>1.6</td> <td>0.56</td> <td>0.36</td> <td>0.1</td> <td>-</td> </tr> </tbody> </table>	Mounting Height	0'	0.5'	1'	2'	3'	4'	5'	6"	69.4	14.4	1.8	0.08	0.03	-	-	12"	15.3	8.6	3.4	0.37	0.08	0.02	-	30"	2.4	2.0	1.6	0.56	0.36	0.1	-
Mounting Height	0'	0.5'	1'	2'	3'	4'	5'																																																											
6"	61.9	13.3	2.0	0.1	0.04	0.01	-																																																											
12"	14.7	8.4	3.3	0.5	0.1	0.03	-																																																											
30"	2.2	2.0	1.6	0.8	0.36	0.15	-																																																											
Mounting Height	0'	0.5'	1'	2'	3'	4'	5'																																																											
6"	69.4	14.4	1.8	0.08	0.03	-	-																																																											
12"	15.3	8.6	3.4	0.37	0.08	0.02	-																																																											
30"	2.4	2.0	1.6	0.56	0.36	0.1	-																																																											

D