

INCANDESCENT / LED 12V HYBRID PATH & SPREAD



15379 OZ - GATE HOUSE™

15446 OZ - ARIES MANOR™

15447 OZ - ARIES MANOR™

<b>Description</b>	Classic estate styling.	An elegant and stately path light featuring solid brass construction, a turned spindle stem.	An elegant and stately indirect path light featuring solid brass construction and a turned spindle stem.
<b>Ordering Guide &amp; Finish</b>	15379 OZ - Olde Bronze®	15446 OZ - Olde Bronze®	15447 OZ - Olde Bronze®
<b>Housing</b>	Cast Brass	Brass with cocoa turned marble accent. Citrine glass.	Brass with cocoa turned marble accent.
<b>Lamp Base</b>	12V S8 wedge base socket	12V T5 wedge base socket	12V T5 wedge base socket
<b>Supplied Lamp</b>	24.4-W(VA) 3156K (15598 CLR) Krypton light source Power usage at 12V AC input VA MAX: 24.4-W(VA)	16.25-W(VA) 921X (17025) Xenon light source Power usage at 12V AC input VA MAX: 16.25-W(VA)	11.6-W(VA) 912X (17023) Xenon light source Power usage at 12V AC input VA MAX: 16.25-W(VA)
<b>Incandescent Lamp Options</b>	18.5-W(VA) 3155K (15599 CLR)	11.6-W(VA) 912X (17023) 6.5-W(VA) 918X (17022) 4-W(VA) 901X (17021)	16.25-W(VA) 921X (17025) 6.5-W(VA) 918X (17022) 4-W(VA) 901X (17021)
<b>LED Lamp Options</b>	2W (18036-13038) see page 159 Compares up to 18.5W Krypton	2W (18039-13041) see page 159 Compares up to 16W Xenon	2W (18039-13041) see page 159 Compares up to 16W Xenon
<b>Wiring</b>	34" of usable #18-2, SPT-1-W leads Cable connector supplied	24" of usable #18-2, SPT-1-W leads Cable connector supplied	24" of usable #18-2, SPT-1-W leads Cable connector supplied
<b>Mounting Acces. Included</b>	14" In-ground stake	8" In-ground stake	8" In-ground stake
<b>Optional Acces.</b>	15601 - Surface Mounting Flange 15607 - Surface Mounting Bracket	15601 - Surface Mounting Flange 15607 - Surface Mounting Bracket	15601 - Surface Mounting Flange 15607 - Surface Mounting Bracket
<b>Notes</b>	U.S. Patent No. D561,371	N/A	N/A
<b>Photometric with Supplied Lamp</b>	Distance from Light 0' 1' 2' 3' 4' 5' 6' 7' 8' Footcandles 8.16 3.43 3.43 1.46 .33 - - - -	Distance from Light 0' 1' 2' 3' 4' 5' 6' 7' 8' Footcandles 0.5 1.1 0.8 0.4 0.1 0 - - - -	Distance from Light 0' 1' 2' 3' 4' 5' 6' 7' 8' Footcandles 6.9 4.9 2.9 1.3 0.4 0.1 - - - -

Denotes fixture is compatible with incandescent or LED lamps.