

INCANDESCENT / LED 12V HYBRID PATH & SPREAD



15314 AZT, MST - SINGLE-TIER LEAF

15436 OZ - INTAGLIO BRASS CROOK NECK

15347 VGB - AINSLEY SQUARE™

<b>Description</b>	Delicate leaf form casts a warm, diffused light along a walkway or near an entryway.	A richly detailed solid and heavy crookneck path light with a brass shade that has been engraved and etched with an organic pattern.	Pierced brass dome and stem and verdigris finish for stylish path lighting.																																																												
<b>Ordering Guide &amp; Finish</b>	15314 AZT - Textured Architectural Bronze 15314 MST - Textured Midnight Spruce™	15436 OZ - Olde Bronze®	15347 VGB - Verdigris with Aged Brass																																																												
<b>Housing</b>	Cast Aluminum	Brass	Brass																																																												
<b>Lamp Base</b>	12V S8 wedge base socket	12V T5 wedge base socket	12V S8 wedge base socket																																																												
<b>Supplied Lamp</b>	24.4-W(VA) 3156K (15598 CLR) Krypton light source Power usage at 12V AC input VA MAX: 24.4-W(VA)	11.6-W(VA) 912X (17023) Xenon light source Power usage at 12V AC input VA MAX: 16.25-W(VA)	24.2-W(VA) 3156K (15598 CLR) Krypton light source Power usage at 12V AC input VA MAX: 24.4-W(VA)																																																												
<b>Incandescent Lamp Options</b>	18.5-W(VA) 3155K (15599 CLR)	16.25-W(VA) 921X (17025) 6.5-W(VA) 918X (17022) 4-W(VA) 901X (17021)	18.5-W(VA) 3155K (15599 CLR)																																																												
<b>LED Lamp Options</b>	2W (18036-13038) see page 159 Compares up to 18.5W Krypton	2W (18039-13041) see page 159 Compares up to 16W Xenon	2W (18036-13038) see page 159 Compares up to 18.5W Krypton																																																												
<b>Wiring</b>	35" of usable #18-2, SPT-1-W leads Cable connector supplied	26" of usable #18-2, SPT-1-W leads Cable connector supplied	32" of usable #18-2, SPT-1-W leads Cable connector supplied																																																												
<b>Mounting Acces. Included</b>	8" In-ground stake	8" In-ground stake	8" In-ground stake																																																												
<b>Optional Acces.</b>	15601 - Surface Mounting Flange 15607 - Surface Mounting Bracket	15601 - Surface Mounting Flange 15607 - Surface Mounting Bracket	15601 - Surface Mounting Flange 15607 - Surface Mounting Bracket																																																												
<b>Notes</b>	N/A	N/A	U.S. Patent Pending																																																												
<b>Photometric with Supplied Lamp</b>	<table border="1"> <tr> <td>Distance from Light</td> <td>1'</td><td>2'</td><td>3'</td><td>4'</td><td>5'</td><td>6'</td><td>7'</td><td>8'</td><td>9'</td> </tr> <tr> <td>Footcandles</td> <td>2.6</td><td>3.2</td><td>1.2</td><td>.5</td><td>.2</td><td>-</td><td>-</td><td>-</td><td>-</td> </tr> </table>	Distance from Light	1'	2'	3'	4'	5'	6'	7'	8'	9'	Footcandles	2.6	3.2	1.2	.5	.2	-	-	-	-	<table border="1"> <tr> <td>Distance from Light</td> <td>0'</td><td>1'</td><td>2'</td><td>3'</td><td>4'</td><td>5'</td><td>6'</td><td>7'</td><td>8'</td> </tr> <tr> <td>Footcandles</td> <td>8.9</td><td>5.3</td><td>2.1</td><td>0.5</td><td>.02</td><td>0</td><td>-</td><td>-</td><td>-</td> </tr> </table>	Distance from Light	0'	1'	2'	3'	4'	5'	6'	7'	8'	Footcandles	8.9	5.3	2.1	0.5	.02	0	-	-	-	<table border="1"> <tr> <td>Distance from Light</td> <td>0'</td><td>1'</td><td>2'</td><td>3'</td><td>4'</td><td>5'</td><td>6'</td><td>7'</td><td>8'</td> </tr> <tr> <td>Footcandles</td> <td>2.7</td><td>1.1</td><td>.3</td><td>.2</td><td>-</td><td>-</td><td>-</td><td>-</td><td>-</td> </tr> </table>	Distance from Light	0'	1'	2'	3'	4'	5'	6'	7'	8'	Footcandles	2.7	1.1	.3	.2	-	-	-	-	-
Distance from Light	1'	2'	3'	4'	5'	6'	7'	8'	9'																																																						
Footcandles	2.6	3.2	1.2	.5	.2	-	-	-	-																																																						
Distance from Light	0'	1'	2'	3'	4'	5'	6'	7'	8'																																																						
Footcandles	8.9	5.3	2.1	0.5	.02	0	-	-	-																																																						
Distance from Light	0'	1'	2'	3'	4'	5'	6'	7'	8'																																																						
Footcandles	2.7	1.1	.3	.2	-	-	-	-	-																																																						

Denotes fixture is compatible with incandescent or LED lamps.