



INCANDESCENT / LED 12V HYBRID PATH & SPREAD



	15429 TZT - CATHEDRAL™	15457 AZT - PIERCED DOME																																								
Description	Transitional styling with draped arches of interwoven bands.	A cast dome sculpted with a floral band and pierced to reveal a trickle of light.																																								
Ordering Guide & Finish	15429 TZT - Textured Tannery Bronze™	15457 AZT - Textured Architectural Bronze™																																								
Housing	Aluminum	Cast Aluminum																																								
Lamp Base	12V T5 wedge base socket 	12V T5 wedge base socket 																																								
Supplied Lamp	11.6-W(VA) 912X (17023) Xenon light source Power usage at 12V AC input VA MAX: 16.25-W(VA)	16.25-W(VA) 921X (17025) Xenon light source Power usage at 12V AC input VA MAX: 16.25-W(VA)																																								
Incandescent Lamp Options	16.25-W(VA) 921X (17025) 6.5-W(VA) 918X (17022) 4-W(VA) 901X (17021)	11.6-W(VA) 912X (17023) 6.5-W(VA) 918X (17022) 4-W(VA) 901X (17021)																																								
LED Lamp Options	2W (18039-13041) see page 159 Compares up to 16W Xenon	2W (18039-13041) see page 159 Compares up to 16W Xenon																																								
Wiring	24" of usable #18-2, SPT-1-W leads. Cable connector supplied	24" of usable #18-2, SPT-1-W leads. Cable connector supplied																																								
Mounting Acces. Included	8" In-ground stake (Included)	8" In-ground stake (Included)																																								
Optional Acces.	15601 - Surface Mounting Flange 15607 - Surface Mounting Bracket	15601 - Surface Mounting Flange 15607 - Surface Mounting Bracket																																								
Photometric with Supplied Lamp	<table border="1"> <tr> <td>Distance from Light</td> <td>0'</td><td>1'</td><td>2'</td><td>3'</td><td>4'</td><td>5'</td><td>6'</td><td>7'</td><td>8'</td> </tr> <tr> <td>Footcandles</td> <td>7.52</td><td>5.42</td><td>0.47</td><td>1.15</td><td>0.32</td><td>0.05</td><td>-</td><td>-</td><td>-</td> </tr> </table>	Distance from Light	0'	1'	2'	3'	4'	5'	6'	7'	8'	Footcandles	7.52	5.42	0.47	1.15	0.32	0.05	-	-	-	<table border="1"> <tr> <td>Distance from Light</td> <td>0'</td><td>1'</td><td>2'</td><td>3'</td><td>4'</td><td>5'</td><td>6'</td><td>7'</td><td>8'</td> </tr> <tr> <td>Footcandles</td> <td>9.36</td><td>5.22</td><td>3.76</td><td>2.02</td><td>0.89</td><td>0.12</td><td>0.05</td><td>-</td><td>-</td> </tr> </table>	Distance from Light	0'	1'	2'	3'	4'	5'	6'	7'	8'	Footcandles	9.36	5.22	3.76	2.02	0.89	0.12	0.05	-	-
Distance from Light	0'	1'	2'	3'	4'	5'	6'	7'	8'																																	
Footcandles	7.52	5.42	0.47	1.15	0.32	0.05	-	-	-																																	
Distance from Light	0'	1'	2'	3'	4'	5'	6'	7'	8'																																	
Footcandles	9.36	5.22	3.76	2.02	0.89	0.12	0.05	-	-																																	

 Denotes fixture is compatible with incandescent or LED lamps.