

INCANDESCENT / LED 12V HYBRID PATH & SPREAD



15450 Tzt - MICA MISSION

15352 Oz - TRADITIONAL LANTERN

15334 Ob - CONCORD LANTERN

<b>Description</b>	A mission style roof combined with glass designed to replicate the amber glow of mica for a warm comfortable exterior look.	Classic elegance complimented by etched seedy glass	Revolutionary design adds an early colonial flair to formal settings.
<b>Ordering Guide &amp; Finish</b>	15450 Tzt - Textured Tannery Bronze™	15352 Oz - Olde Bronze®	15334 Ob - Olde Brick®
<b>Housing</b>	Cast Aluminum and mica finished glass	Brass with etched seedy glass	Brass with stainless steel rods and seedy glass
<b>Lamp Base</b>	12V T5 wedge base socket	12V S8 wedge base socket	12V T5 wedge base socket
<b>Supplied Lamp</b>	11.6-W(VA) 912X (17023) Xenon light source Power usage at 12V AC input VA MAX: 16.25-W(VA)	18.5-W(VA) 3155K (15599 CLR) Krypton light source Power usage at 12V AC input VA MAX: 18.5-W(VA)	6.5-W(VA) 918X (17022) Xenon light source Power usage at 12V AC input VA MAX: 6.5-W(VA)
<b>Incandescent Lamp Options</b>	16.25-W(VA) 921X (17025) 6.5-W(VA) 918X (17022) 4-W(VA) 901X (17021)	N/A	4-W(VA) 901X (17022)
<b>LED Lamp Options</b>	N/A	2W (18036-13038) see page 159 Compares up to 18.5W Krypton	2W (18039-13041) see page 159 Compares up to 16W Xenon
<b>Wiring</b>	22" of usable #18-2, SPT-1-W leads Cable connector supplied	24" of usable #18-2, SPT-1-W leads Cable connector supplied	20" of usable #18-2, SPT-1-W leads Cable connector supplied
<b>Mounting Acces. Included</b>	8" In-ground stake	8" In-ground stake	8" In-ground stake
<b>Optional Acces.</b>	15601 - Surface Mounting Flange 15607 - Surface Mounting Bracket	15601 - Surface Mounting Flange 15607 - Surface Mounting Bracket	15601 - Surface Mounting Flange 15607 - Surface Mounting Bracket
<b>Notes</b>	N/A	U.S. Patent No. D420,160	N/A
<b>Photometric with Supplied Lamp</b>	Distance from Light 0' 1' 2' 3' 4' 5' 6' 7' 8' Footcandles 1.34 1.61 1.63 0.86 0.46 0.28 0.07 0.07 -	Distance from Light .5' 1' 2' 3' 4' 5' 6' 7' 8' Footcandles 2.7 1.3 .3 .1 - - - - -	Distance from Light 1' 2' 3' 4' 5' 6' 7' 8' 9' Footcandles 20.9 4.7 .6 .2 - - - - -

Denotes fixture is compatible with incandescent or LED lamps.