

INCANDESCENT / LED 12V HYBRID PATH & SPREAD



INCANDESCENT/LED 12V HYBRID PATH & SPREAD

P

	15005 AZT, BKT - FUNDAMENTALS™	15315 AZT, AZT6, BE, BKT - SIDE MOUNT																																																																																
Description	Louvers direct tiers of light downward for well-shielded, dramatic lighting. Blends nicely with shrubs or flowers along a pathway. Available in stem or deck mount or as a bollard. Mounting stems and bollard kits sold separately. Coordinates with matching deck light 15065 on page 109.	A popular design in a side-mount fixture for more directional lighting without glare. Coordinates with matching deck light 15065 on page 109.																																																																																
Ordering Guide & Finish	15005 AZT - Textured Architectural Bronze 15005 BKT - Textured Black	15315 AZT - Textured Architectural Bronze 15315 AZT6 - Same as 15315 AZT. Bulk packed in 6 (unbreakable master) 15315 BKT - Textured Black																																																																																
Housing	Cast Aluminum with molded ribbed diffuser of clear UV stabilized high impact resistant polycarbonate	Cast Aluminum																																																																																
Lamp Base	12V S8 wedge base socket	12V S8 wedge base socket																																																																																
Supplied Lamp	24.4-W(VA) 3156K (15598 CLR) Krypton light source Power usage at 12V AC input VA MAX: 24.4-W(VA)	24.4-W(VA) 3156K (15598 CLR) Krypton light source Power usage at 12V AC input VA MAX: 24.4-W(VA)																																																																																
Incandescent Lamp Options	18.5-W(VA) 3155K (15599 CLR)	18.5-W(VA) 3155K (15599 CLR)																																																																																
LED Lamp Options	2W (18036-13038) see page 159 Compares up to 18.5W Krypton	2W (18036-13038) see page 159 Compares up to 18.5W Krypton																																																																																
Wiring	52" of usable #18-2, SPT-1-W leads. Cable connector supplied	35" of usable #18-2, SPT-1-W leads. Cable connector supplied																																																																																
Mounting Acces. Included	NA	8" In-ground stake and 18" stem																																																																																
Optional Acces.	15656, 15657, 15658 or 15570 - Stems 15575 BK, 15576 BK or 15578 - Stakes 15665, 15666 or 15667 - Bollard 15671 ST - Bollard Template Kit 15601 - Surface Mounting Flange 15602 - Flange Mounting Nipple 15607 - Surface Mounting Bracket	15601 - Surface Mounting Flange 15607 - Surface Mounting Bracket																																																																																
Integrated LED Option	NA	15815 - on Page 15																																																																																
Photometric with Supplied Lamp	<table border="1"> <thead> <tr> <th>Stem Height</th> <th>1'</th> <th>2'</th> <th>3'</th> <th>4'</th> <th>5'</th> <th>6'</th> <th>7'</th> <th>8'</th> <th>9'</th> </tr> </thead> <tbody> <tr> <td>12"</td> <td>2.1</td> <td>.93</td> <td>.67</td> <td>.18</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>18"</td> <td>1.8</td> <td>.73</td> <td>.4</td> <td>.27</td> <td>0.3</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>24"</td> <td>1.2</td> <td>.67</td> <td>.33</td> <td>.35</td> <td>.27</td> <td>.15</td> <td>-</td> <td>-</td> <td>-</td> </tr> </tbody> </table>	Stem Height	1'	2'	3'	4'	5'	6'	7'	8'	9'	12"	2.1	.93	.67	.18	-	-	-	-	-	18"	1.8	.73	.4	.27	0.3	-	-	-	-	24"	1.2	.67	.33	.35	.27	.15	-	-	-	<table border="1"> <thead> <tr> <th>Stem Height</th> <th>1'</th> <th>2'</th> <th>3'</th> <th>4'</th> <th>5'</th> <th>6'</th> <th>7'</th> <th>8'</th> <th>9'</th> </tr> </thead> <tbody> <tr> <td>12"</td> <td>18.7</td> <td>4.3</td> <td>1.4</td> <td>.27</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>18" (as supplied)</td> <td>15</td> <td>5.2</td> <td>1.8</td> <td>.8</td> <td>.27</td> <td>.03</td> <td>-</td> <td>-</td> <td>-</td> </tr> <tr> <td>24"</td> <td>11.6</td> <td>5.1</td> <td>2.2</td> <td>.97</td> <td>.48</td> <td>.2</td> <td>.07</td> <td>-</td> <td>-</td> </tr> </tbody> </table>	Stem Height	1'	2'	3'	4'	5'	6'	7'	8'	9'	12"	18.7	4.3	1.4	.27	-	-	-	-	-	18" (as supplied)	15	5.2	1.8	.8	.27	.03	-	-	-	24"	11.6	5.1	2.2	.97	.48	.2	.07	-	-
Stem Height	1'	2'	3'	4'	5'	6'	7'	8'	9'																																																																									
12"	2.1	.93	.67	.18	-	-	-	-	-																																																																									
18"	1.8	.73	.4	.27	0.3	-	-	-	-																																																																									
24"	1.2	.67	.33	.35	.27	.15	-	-	-																																																																									
Stem Height	1'	2'	3'	4'	5'	6'	7'	8'	9'																																																																									
12"	18.7	4.3	1.4	.27	-	-	-	-	-																																																																									
18" (as supplied)	15	5.2	1.8	.8	.27	.03	-	-	-																																																																									
24"	11.6	5.1	2.2	.97	.48	.2	.07	-	-																																																																									

Denotes fixture is compatible with incandescent or LED lamps.