

## Saws & Blades

### Reciprocating Saw Blades

- Bi-metal blades offer different cutting applications of steel and wood
- Bi-metal construction for long cutting life
- Heat and wear resistant
- Shock resistant teeth resist strippage
- 1/2" universal shank to fit all popular reciprocating saw tools
- Made in USA



Cat. No.	Application	Teeth Per Inch	Blade Length	Blade Width	Blade Thickness	Package Quantity	Weight
31716	Wood with Nails	6	6" (152.4 mm)	3/4" (19.1 mm)	0.050" (1.27 mm)	5	0.23 lb (0.10 kg)
31751 <b>NEW!</b>	Wood, Wood with Nails	6	9" (228.6 mm)	3/4" (19.1 mm)	0.05" (1.27 mm)	5	0.30 lb (0.14 kg)
31761 <b>NEW!</b>	Wood with Nails	6	12" (304.8 mm)	3/4" (19.1 mm)	0.05" (1.27 mm)	5	0.50 lb (0.23 kg)
31731 <b>NEW!</b>	Wood with Nails, Heavy Gauge Metals	10/14	6" (152.4 mm)	3/4" (19.1 mm)	0.050" (1.27 mm)	5	0.25 lb (0.11 kg)
31741 <b>NEW!</b>	Wood with Nails, Heavy Gauge Metals	10/14	8" (203.2 mm)	3/4" (19.1 mm)	0.05" (1.27 mm)	5	0.40 lb (0.18 kg)
31727 <b>NEW!</b>	Heavy Gauge Metals	14	6" (152.4 mm)	3/4" (19.1 mm)	0.035" (0.89 mm)	5	0.25 lbs. (0.11 kg)
31755 <b>NEW!</b>	Heavy Gauge Metals	14	9" (228.6 mm)	1" (25.4 mm)	0.042" (1.07 mm)	5	0.50 lb (0.23 kg)
31728	Heavy Gauge Metals	18	6" (152.4 mm)	3/4" (19.1 mm)	0.035" (0.89 mm)	5	0.41 lb (0.19 kg)
31739 <b>NEW!</b>	Heavy Gauge Metals	18	8" (203.2 mm)	3/4" (19.1 mm)	0.035" (0.89 mm)	5	0.30 lb (0.14 kg)
31734	18 Gauge and Under	24	6" (152.4 mm)	3/4" (19.1 mm)	0.035" (0.89 mm)	5	0.10 lb (0.05 kg)

NOTE: Read and follow safety instructions in power tool owner's manual.

### Jab Saw

- Cuts drywall, wallboard, plywood and plastic
- Triple ground teeth for a fast cut
- Blade cuts in both directions (push and pull)
- Hardened, carbon-steel blade for durability
- Hardened, beveled blade point for scoring and plunge cuts
- Comfort cushion grip with thumb groove
- Flat-end grip for palming or punching through drywall



Cat. No.	Blade Length	Overall Length	Weight
725	6" (152.4 mm)	12" (304.8 mm)	0.31 lb (0.14 kg)

### Magic-Slot Compass Saws

- Magic-Slot design allows fast blade changing without removing thumbscrew
- Strong, lightweight, die-cast zinc handle with blue finish is contoured for comfort
- Cat. No. 703 comes with Cat. No. 706 8" blade
- Cat. No. 702 can be used with Magic-Slot cut-in or general-purpose blades only
- Made in USA



Cat. No.	Teeth Per Inch	Overall Length	Weight
703	10	13" (330.2 mm)	1.2 lb (0.5 kg)
Magic-Slot Compass Saw Handle			
702	—	5" (127.0 mm)	1.1 lb (0.5 kg)

### Compass Saw Replacement Blades

- For cutting through wallboard or Masonite to install wiring, outlet boxes, etc.
- Tough high-quality carbon steel
- Pointed starter tip
- Fits Magic-Slot compass saw handle Cat. No. 702



Cat. No.	Teeth Per Inch	Blade Length	Weight
704	8	12" (304.8 mm)	0.14 lb (0.06 kg)
705	10	12" (304.8 mm)	0.14 lb (0.06 kg)
706	10	8" (203.2 mm)	1.4 oz (40 g)
707	10	10" (254.0 mm)	0.12 lb (0.05 kg)
709	10	4" (101.6 mm)	1.0 oz (28 g)