

Cushion-Grip Screwdrivers

Demolition Screwdrivers

Includes core Cushion-Grip screwdriver features plus:

- Engineered, manufactured and tested for prying, chiseling and punching
- Plated metal strike cap to protect handle from hammer blows
- Heat treated metal shaft runs complete length of handle to metal strike cap to transfer metal strike force

Shank

Length

3" (76.2 mm)

2" (50.8 mm)

3" (76.2 mm)

4" (101.6 mm)

6" (152.4 mm)

Shank Type

Round

Round

Round

Round

Round

Overall

Length

6-1/2" (165.1 mm)

5-1/2" (139.7 mm)

6-1/2" (165.1 mm)

7-1/2" (190.5 mm)

9-1/2" (241.3 mm)



Cat. No.	Tip	Shank	Shank	Overall	Weight	Cat. No.			Weight
No.	Туре	Туре	Length	Length		32008			0.70 lb
602-4DD	1/4" (6.4 mm) Cabinet	Round	4" (101.6 mm)	9" (228.6 mm)	0.37 lb (0.17 kg)				(0.32 kg)
602-7DD	5/16" (7.9 mm) Keystone	Round	7" (177.8 mm)	12-3/8" (314.3 mm)	0.56 lb (0.25 kg)		Cat. No.	Description	
6034DD	#2 Phillips	Round	4" (101.6 mm)	9" (228.6 mm)	0.37 lb (0.17 kg)		602-4DD	1/4" Keystone Demolition Driver, 4" Shank	-
							6034DD	#2 Phillips Demolition Driver, 4" Shank	-

Electronics Screwdrivers

Includes core Cushion-Grip screwdriver features plus:

Rotating cap for optimum and precise control

G =	Cat. No.	at. No. Set Contains				
Weight	85614	5 Piece Ele	0.80 lb (0.36 kg)			
		Cat. No.	Description			
0.80 oz (22.7 g)		614-2	1/16" Slotted Electronics Screwdriver, 2" Shank			
0.80 oz (22.7 g)		614-3	3/32" Slotted Electronics Screwdriver, 3" Shank			
0.80 oz (22.7 g)		614-4	1/8" Electronics Screwdriver 4" Shank			
0.80 oz (22.7 g)		614-6	1/8" Electronics Screwdriver 6" Shank			
0.80 oz (22.7 g)		613-3	#0 Phillips Electronics Screwdriver, 3" Shank			

602-7DD

614-6

620-4

GINSLEINAT

Coated Screwdrivers

1/16" (1.59 mm) Cabinet

3/32" (2.4 mm) Cabinet

1/8" (3.2 mm) Cabinet

1/8" (3.2 mm) Cabinet

Cat. No.

613-3

614-2

614-3

614-4

614-6

Tip Type

#0 Phillips

Includes core Cushion-Grip screwdriver features plus:

- Plastic coated for circuit protection only. NOT INSULATED
- Special plastic coating resists cutting, cracking and chipping
- Thin coating permits use in confined areas

Cat. No.	Тір Туре	Shank Type	Shank Length	Overall Length	Weight
620-3	3/16" (4.8 mm) Cabinet	Round	3" (76.2 mm)	6-3/4" (171.5 mm)	0.15 lb (0.07 kg)
620-4	1/4" (6.4 mm) Cabinet	Round	4" (101.6 mm)	8-11/32" (211.9 mm)	0.20 lb (0.09 kg)
620-6	5/16" (7.9 mm) Cabinet	Round	6" (152.4 mm)	10-15/16" (277.8 mm)	0.40 lb (0.18 kg)
620-8	3/8" (9.52 mm) Cabinet	Round	8" (203.2 mm)	13-7/16" (341.3 mm)	0.60 lb (0.27 kg)
621-6	3/16" (4.8 mm) Cabinet	Round	6" (152.4 mm)	9-3/4" (247.7 mm)	0.20 lb (0.09 kg)
621-8	3/16" (4.8 mm) Cabinet	Round	8" (203.2 mm)	11-3/4" (298.5 mm)	0.20 lb (0.09 kg)

2-in-1 Rapi-Driv®

- Interchangeable bit holder allows quick switching between tip styles and works with other standard size bits
- Crank-action handle allows you to spin screws fast with one hand
- •



See page 295 for additional information on warnings.

