



ALUMICONN®

Aluminum to Copper Lug

- Secure, mechanical connection of conductors
- Runs approximately 25°F cooler than purple twist-ons*
- Provides a safer connection
- Separate ports eliminate intermixing of conductors
- One piece for easy installation
- Dielectric silicone inhibitor reduces corrosion of connection
- Tin-plated lug and nickel-plated screws
- Max voltage: 300V
- Aluminum Wire Range: #12 - #10 solid AWG
- Copper Wire Range: #18 - #10 solid and stranded AWG
- UL 486C Listed to meet U.S. and Canadian standards
- Temperature rating of insulating material: 105°C
- Suitable for aluminum to aluminum, aluminum to copper, and copper to copper wire splices
- Approved by CPSC and insurance companies
- Available in 2-Port and 3-Port styles

- SKU# 95025 AlumiConn 2 Port- Bag of 25
- SKU# 95035 AlumiConn 2 Port- Box of 100
- SKU# 95045 AlumiConn 2 Port- Box of 1000
- SKU# 95085 AlumiConn 2 Port- Box of 2500
- SKU# 95104 AlumiConn 3 Port- Card of 2
- SKU# 95110 AlumiConn 3 Port- Card of 10
- SKU# 95125 AlumiConn 3 Port- Bag of 25
- SKU# 95135 AlumiConn 3 Port- Box of 100
- SKU# 95145 AlumiConn 3 Port- Box of 1,000
- SKU# 95185 AlumiConn 3 Port- Box of 2,500



MADE IN USA

U.S. Pat. Pending. All other trademarks, U.S. and Foreign Patents apply. All Rights Reserved.



3 Port*

AlumiConn
Min #18/Max #10



2 Port

**NEW FOR
2014!**



- ✓ UL LISTED.
- ✓ INSURANCE COMPANY ENDORSED.
- ✓ CONSUMER PRODUCT SAFETY COMMISSION APPROVED.
- ✓ COMPACT FIT.
- ✓ LOW COST.
- ✓ SECURE CONNECTION.
- ✓ FIRE PREVENTATIVE.
- ✓ PERMANENT SOLUTION.



For more information, scan here.