

PVC BALL VALVES

T/S-603

ISO 9002



PVC True Union Ball Valve
Pressure Rating: 150 PSI at 73° F
Max Service Temp: 140° F
Fits schedule 40 or 80 PVC Pipe
Threaded or solvent ends included***
*Teflon™ seats
EPDM O-rings
Grey color UPVC resin
Sizes: Threaded 1/2" to 4"
Solvent 1/2" to 4"

***Threaded adaptors for
Sizes 2-1/2" to 4" sold
separately

**Also available with **Viton O-rings
(Model T/S-603V)**
Sizes: Threaded 1/2" to 2"
Solvent 1/2" to 2"

S-643

ISO 9002



PVC Flanged True Union Ball Valve
Pressure Rating: 150 PSI at 73° F
Max Service Temp: 140° F
Fits schedule 40 or 80 PVC pipe
Class 125 Flanged Ends
*Teflon™ seats
EPDM O-rings
Grey color UPVC resin
Sizes: 1/2" to 4"

T/S-645

ISO 9002



PVC Single Union Ball Valve
Pressure Rating: 150 PSI at 73° F
Max Service Temp: 140° F
Fits schedule 40 or 80 PVC pipe
*Teflon™ seats
EPDM O-rings
Grey color UPVC resin
Sizes: Threaded 1/2" to 2"
Solvent 1/2" to 2"

T/S-602

ISO 9002



Grey PVC Compact Ball Valve
Pressure Rating: 150 PSI at 73° F
Max Service Temp: 140° F
NSF Approved
Fits schedule 40 or 80 PVC pipe
*Teflon™ seats
EPDM O-rings
Grey color UPVC resin
Sizes: Threaded 1/2" to 2"
Solvent 1/2" to 2"

T/S-600

ISO 9002



White PVC Compact Ball Valve
Pressure Rating: 150 PSI at 73° F
Max Service Temp: 140° F
NSF approved
EPDM seats
EPDM stem O-ring
White color PVC resin
Sizes: Threaded 1/2" to 2"
Solvent 1/2" to 2"

T/S-601

ISO 9002



White PVC Compact Ball Valve
Pressure Rating: 150 PSI at 73° F
Max Service Temp: 140° F
EPDM seats
EPDM stem O-ring
White color PVC resin
Sizes: Threaded 1/4" to 4"
Solvent 1/2" to 4"

*Teflon is a registered trademark of DuPont

**Viton is a registered trademark of Dupont