

PVC BUTTERFLY VALVES

S-650

ISO 9002



Lever Operated PVC Butterfly Valve

Pressure Rating: 150 PSI at 73° F
 Max Service Temp: 140° F

Wafer style
 Bubble tight seal
 Bi-directional flow

EPDM seat
 EPDM O-rings

Grey color UPVC resin

Sizes: 2" to 8"

S-651

ISO 9002



Gear Operated PVC Butterfly Valve

Pressure Rating: 150 PSI at 73° F
 Max Service Temp: 140° F

Wafer style
 Bubble tight seal
 Bi-directional flow

EPDM seat
 EPDM O-rings

Grey color UPVC resin

Sizes: 8" to 12"

PVC CHECK VALVES

T/S-611

ISO 9002



PVC In-Line Check Valve

Pressure Rating: 150 PSI at 73° F
 Max Service Temp: 140° F

Fits schedule 40 or 80 PVC pipe
 1/2 lb. Stainless steel spring
 EPDM seal

Can be installed vertically
 or horizontally

White color PVC resin

Sizes: Threaded 1/2" to 2"
 Solvent 1/2" to 2"

NOT SUITABLE
 FOR COMPRESSED
 AIR SERVICE

S-640

ISO 9002



PVC Backwater Valve

UPC/IAPMO Listed
 IPC Listed

For DWV installation at pressures
 less than 50 PSI

Access cap
 Neoprene O-rings

Sizes: Solvent 1-1/2" to 6"

**Also available with 16"
 access sleeve & lid
 (Model: S-641)**

Sizes: Solvent 2", 3" & 4"

ABS CHECK VALVES

T/S-655

ISO 9002



PVC Ball Check Valve

Pressure Rating: 150 PSI at 73° F
 Max Service Temp: 140° F

Fits schedule 40 or 80 PVC pipe
 EPDM seal

Grey color UPVC resin

Sizes: Threaded 1/2" to 2"
 Solvent 1/2" to 2"

**Can be converted to a Foot Valve
 by the addition of an optional
 UPVC Screen**

S-660

ISO 9002



ABS Backwater Valve

For DWV installation at pressures
 less than 50 PSI

Access cap
 Neoprene O-rings

Sizes: Solvent 3" & 4"

**Also available with 16"
 access sleeve & lid
 (Model: S-661)**

Sizes: Solvent 3" & 4"