

## SPECIALTY PRODUCTS

### Compression Repair Couplings



Compression Repair Couplings  
Available in Galvanized Malleable  
Iron or Brass

125 CWP  
Max Temp 200° F

Long Pattern

Sizes: Galvanized 1/2" to 2" (IPS)

Brass 3/8" to 1-1/2" (IPS)  
1/2" to 2" (CTS)

### Compression Repair Couplings

ISO 9002



Compression Repair Couplings  
Available in PVC or CPVC

Pressure Rating: 150 PSI at 73° F  
Max Service Temp: PVC 140° F  
CPVC 180° F

Long Pattern

CPVC are NSF approved

Sizes: PVC 1/2" to 6" (IPS)

CPVC 1/2" to 3/4" (CTS)

### PVC Expansion Repair Couplings



Expansion Repair Couplings  
Available in PVC

Pressure rating: 150 PSI @ 73° F  
Max service temp: 140 F

Adjustable spigot end  
Buna-N O-ring

White color PVC resin

Sizes: spigot x socket 1/2" to 2"

### T-30, T-31, T-32 Float Valve BRONZE

ISO 9002



Float Valves Male or Female  
Inlet x Male or Plain Outlet

125 CWP

Buna-N Seat

\*Adjustable float rod arm

Sizes: 3/8" to 2"

\*Float rods and floats sold separately

### Tankless Water Heater Isolation Valve Kit BRASS



Tankless Water Heater  
Isolation Valves Kit (Pair)

Full port ball valve design

Integral drain valve  
w/tethered cap

Union connections

PRV included

Sizes: 3/4"

### Square Head Plugs BRASS



Raised or Countersunk Square  
Head Plugs

Southern Code

Cored, cleanout style

Sizes: 1-1/4" to 8"

