

## SPECIALTY BALL VALVES

### T/S-2000 FORGED BRASS

ISO 9002



Full Port  
Gland Follower Design

MSS SP-110  
600 CWP  
150 WSP

Blow-out proof stem  
PTFE seats

Sizes: Threaded 1/4" to 4"  
Solder 1/2" to 4"

CSA Certified  
UL Listed  
Meets ANSI / NSF 61-8

### T-1002LD FORGED BRASS

ISO 9002



Full Port  
Gland Follower Design

MSS SP-110  
600 CWP  
150 WSP

Blow-out proof stem  
PTFE seats

Locking device

Sizes: Threaded 1/4" to 2"

CSA Certified,  
UL Listed  
FM Approved

**Also Available: T-1002STLD  
316 Stainless steel ball & stem  
and Locking device**

### T/S-1002FLG BRASS

ISO 9002



Full Port Flanged Isolation Valve  
Gland Follower Design

MSS SP-110  
600 CWP  
150 WSP

Blow-out proof stem  
PTFE seats

Bolt set included

Sizes: Threaded 3/4" to 1-1/4"  
Solder 3/4" to 1-1/4"

**Also Available: T/S-2012RFLG BRASS  
Drainable with  
Rotating Flange**



### T-1001LD FORGED BRASS

ISO 9002



Full Port  
O-Ring Design

MSS SP-110  
600 CWP  
150 WSP

Blow-out proof stem  
\*Dyneon™ TFM PTFE seats

Locking device

Sizes: Threaded 1/2" to 2"

CSA Certified to  
ANSI/NSF 61  
UL Listed  
FM Approved

### T-1002CC SPECIALITY - FORGED BRASS

ISO 9002



Full Port  
Gland Follower Design

MSS SP-110  
600 CWP (Body)  
200 CWP rated end connections

Blow-out proof stem  
PTFE seats

Cap & chain

Sizes: Threaded  
3/4" FIP x 3/4" GHT