

T-2006NL No Lead & DZR Forged Brass PEX x PEX Full Port Ball Valve with Tee Handle



Maintenance-free dual EPDM® O-ring stem seal, zinc plated steel tee handle, CWP 400 PSI, Third Party certified no lead ANSI/NSF 61-G & DZR ANSI/NSF 14, IAPMO. ASTM F1806. Configuration and Sizes: PEX x PEX, 1/2" - 3/4".

T-2007NL No Lead & DZR Forged Brass PEX x PEX Drain Full Port Ball Valve with Tee Handle



Maintenance-free dual EPDM® O-ring stem seal, zinc plated steel tee handle, CWP 400 PSI, with drain. Third Party certified no lead ANSI/NSF 61-G & DZR ANSI/NSF 14, IAPMO. ASTM F1806. Configuration and Sizes: PEX x PEX, 1/2" - 1".

T-2007NL No Lead & DZR Forged Brass Sweat x PEX Full Port Ball Valve with Drain



Maintenance-free dual EPDM® O-ring stem seal, zinc plated steel handle with vinyl sleeve CWP 400 PSI, with drain. Third Party certified no lead ANSI/NSF 61-G & DZR ANSI/NSF 14, IAPMO. ASTM F1806. Configuration and Sizes: Sweat x PEX, 1/2" - 1".

T-2005NL No Lead & DZR Forged Brass MNPT x PEX Full Port Ball Valve



Maintenance-free dual EPDM® O-ring stem seal, zinc plated steel handle with vinyl sleeve. Third Party certified no lead ANSI/NSF 61-G & DZR ANSI/NSF 14, IAPMO. CWP 400 PSI. ASTM F1806. Configuration and Sizes: MNPT x PEX, 1/2" - 1".

T-2008NL No Lead & DZR Forged Brass PEX x PEX Drop Ear Full Port Ball Valve



Maintenance-free dual EPDM® O-ring stem seal, zinc plated steel handle with vinyl sleeve and drop ears. CWP 400 PSI. Third Party certified no lead ANSI/NSF 61-G & DZR ANSI/NSF 14, IAPMO. ASTM F1806. Configuration and Sizes: PEX x PEX, 1/2" - 1".