

Accessories

Double-Float Piggyback Mechanical Float Switch



Applications

- Pump control

Features

- Controls pumps up to 1 hp (120 V) and 2 hp (230 V)
- Adjustable pumping range of 1.75" (4.4 cm) to 48" (122 cm)
- Consists of two floats, one of which contains a holding relay, enabling the floats to function in series
- and CSA listing

Item #	Model	Volts	Max. Amps
14940410	15DFMMD1WP	115	13
14940411	15DFMMD2WOP	230 (w/o plug)	13

Sump Pump Switch Repair Kit



Applications

- Switch repair kit

Features

- Includes pressure switch bracket assembly, screw, diaphragm and O-ring

Item #	Model	Repairs Pumps	Housing
599300	SPRK-1	6-CIA, 8-CIA and 8-CBA	✓
599310	SPRK-1-ML	6-CIA-ML (used in WRSC-6)	✓
599320	SPRK-2	5-ASP, 6-CIA, 8-CIA and 8-CBA	-
599314	SPRK-2-ML	6-CIA-ML (used in WRSC-6)	-
599350	SPRK-3	10-CIA and 12-CBA	✓

Vertical Diaphragm Switch



Applications

- For automatic control of a pump in water and sewage effluent applications

Features

- Designed to operate in applications with limited space, such as small sump chambers
- The VDS features models with either a 6" (15.2 cm) or 10" (25.4 cm) pumping range, max 1/2 hp, 13 amps
- UL and CSA listing

Item #	Model	Volts	Cord	Pumping Range
599165	VDS1006	115	10' 3 m	6" 15.2 mm
599168	VDS1010	115	10' 3 m	10" 25.4 mm
599166	VDS1506	115	15' 4.6 m	6" 15.2 mm
599169	VDS1510	115	15' 4.6 m	10" 25.4 mm
599167	VDS2010	115	20' 6 m	10" 25.4 mm

Sump Pump Discharge Kits



Applications

- Discharging water out of the basement sump

Features

- Kit work with all types of sump pumps
- Kit includes 1-1/4" x 24' (31.7 mm x 7.3 m) corrugated polyethylene hose, ABS threaded 1-1/2" MNPT (38 mm) x 1-1/4" (31.7 mm) barbed adapter and 1-1/4" MNPT (31.7 mm) x 1-1/4" (31.7 mm) barbed adapter and galvanized steel clamp

Item #	Model	NPT
599303	SPDK	1-1/4"
		31.7 mm
		1-1/2"
		38 mm