

## LE70-Series Electrical Data

MODEL	HP	VOLTAGE	PHASE	FULL LOAD AMPS	LOCKED ROTOR AMPS	THERMAL OVERLOAD TEMP	STATOR WINDING CLASS	CORD LENGTH FT	DISCHARGE	AUTOMATIC
LE71A2	3/4	115	1	12	29.1	105°C 221°F	B	10	2"	YES
LE71A2-2	3/4	115	1	12	29.1	105°C 221°F	B	25	2"	YES
LE71A2-3	3/4	115	1	12	29.1	105°C 221°F	B	35	2"	YES
LE71M2	3/4	115	1	12	29.1	105°C 221°F	B	10	2"	NO
LE71M2-2	3/4	115	1	12	29.1	105°C 221°F	B	25	2"	NO
LE71M2-3	3/4	115	1	12	29.1	105°C 221°F	B	35	2"	NO
LE71A3	3/4	115	1	12	29.1	105°C 221°F	B	10	3"	YES
LE71A3-2	3/4	115	1	12	29.1	105°C 221°F	B	25	3"	YES
LE71A3-3	3/4	115	1	12	29.1	105°C 221°F	B	35	3"	YES
LE71M3	3/4	115	1	12	29.1	105°C 221°F	B	10	3"	NO
LE71M3-2	3/4	115	1	12	29.1	105°C 221°F	B	25	3"	NO
LE71M3-3	3/4	115	1	12	29.1	105°C 221°F	B	35	3"	NO
LE72A2	3/4	208-230	1	6	13.5	105°C 221°F	B	10	2"	YES
LE72A2-2	3/4	208-230	1	6	13.5	105°C 221°F	B	25	2"	YES
LE72A2-3	3/4	208-230	1	6	13.5	105°C 221°F	B	35	2"	YES
LE72M2	3/4	208-230	1	6	13.5	105°C 221°F	B	10	2"	NO
LE72M2-2	3/4	208-230	1	6	13.5	105°C 221°F	B	25	2"	NO
LE72M2-3	3/4	208-230	1	6	13.5	105°C 221°F	B	35	2"	NO
LE72A3	3/4	208-230	1	6	13.5	105°C 221°F	B	10	3"	YES
LE72A3-2	3/4	208-230	1	6	13.5	105°C 221°F	B	25	3"	YES
LE72A3-3	3/4	208-230	1	6	13.5	105°C 221°F	B	35	3"	YES
LE72M3	3/4	208-230	1	6	13.5	105°C 221°F	B	10	3"	NO
LE72M3-2	3/4	208-230	1	6	13.5	105°C 221°F	B	25	3"	NO
LE72M3-3	3/4	208-230	1	6	13.5	105°C 221°F	B	35	3"	NO
LE73M2-2	3/4	208-230	3	4.1	14.7	N/A	B	25	2"	NO
LE73M2-3	3/4	208-230	3	4.1	14.7	N/A	B	35	2"	NO
LE73M3-2	3/4	208-230	3	4.1	14.7	N/A	B	25	3"	NO
LE73M3-3	3/4	208-230	3	4.1	14.7	N/A	B	35	3"	NO
LE74M2-2	3/4	440-480	3	2.1	7.4	N/A	B	25	2"	NO
LE74M2-3	3/4	440-480	3	2.1	7.4	N/A	B	35	2"	NO
LE74M3-2	3/4	440-480	3	2.1	7.4	N/A	B	25	3"	NO
LE74M3-3	3/4	440-480	3	2.1	7.4	N/A	B	35	3"	NO