

Lomancool™ 2000



2000

Lomanco® Standard Power Vents

Lomanco® Standard Power Vents are designed for quiet operation and high volume air removal. Lomanco offers two styles of electric power vents—the Lomancool™ 2000 and the 1800 Add-A-Vent. The Lomancool™ 2000 is a roof mount power vent and the 1800 is designed to be mounted behind an existing vent to add powered ventilation to a gable.

Features—Lomanco® Standard Power Vents are made of all aluminum construction. Other common features include a 5 year limited warranty, balanced fan blades for quiet operation, and an American-made motor. An optional humidistat is available for both the 2000 and the 1800. The Lomancool™ 2000TH comes equipped with an adjustable thermostat/humidistat combo control to accommodate individual attic humidity levels.

Installation—Lomanco® Standard Power Vents are equipped with an adjustable thermostat that features a “push-to-test” button, allowing homeowners to make sure the unit is operating properly.

Available Colors



- ▶ Deep drawn flange and unique rain shield keep water out.
- ▶ Factory-set adjustable thermostat (switches on at 100 degrees and off at 85 degrees).
- ▶ Adjustable humidistat settings are: minimum 80%, normal 42%, and maximum 20%.
- ▶ 8x8 aluminum screen attached for insect protection.
- ▶ 2000TH model equipped with thermostat/humidistat combo switch.
- ▶ 5 Year limited warranty.

How many Power Vents do you need?

Your attic floor space to be ventilated in square feet.

1000 | 1500 | 2000 | 2500 | 3000 | 3500

POWER VENT EXHAUST SYSTEM

2000	1	2	2	3	3	4
1800	1	NR	NR	NR	NR	NR

POWER VENT INTAKE SYSTEM

C416	31	62	62	93	93	123
C616	21	42	42	63	63	84
C816	12	24	24	36	36	48
105/190	11	22	22	32	32	43
140	9	18	18	27	27	35
SV-10	13	25	25	37	37	49

Add-A-Vent 1800

- ▶ Factory-set adjustable thermostat (switches on at 100 degrees and off at 85 degrees).
- ▶ Can be mounted in horizontal or vertical positions on either 16" or 24" on center framing members.
- ▶ Optional humidistat is adjustable to fit individual attic humidity levels.
- ▶ Designed to mount behind existing gable louver.
- ▶ 5 year limited warranty.




1800

Copper 2000



Available on special order

Model	Amps	Motor		Volts	Base (in.)	Fan Blades	
		HP	RPM			No.	DIA. (in.)
2000* †	3.4	1/10	1100	120	20 x 23	5	12
2000TH †	3.4	1/10	1100	120	20 x 23	5	12
1800	3.4	1/10	1100	120	—	5	12



Scan this QR Code with your smartphone to instantly view the most current information on the vent of your choice.

