





Shown actual size: Skylark dimmer and 1-gang Claro wallplate in White (WH).

Product family features


- Rocker switch returns light to light level indicated by slider on preset dimmers
- Slide up to brighten, down to dim
- C•L® and eco-dim® models available
- Coordinating Claro® and Stainless Steel wallplates only available separately
- Custom engraving available for wallplates, see p. 237

Control types


 Single-pole (one location)


 3-way or 4-way (two or more locations)


Direct load type compatibility


 Incandescent/halogen lighting

 Dimmable CFL/LED lighting (screw-base)


 Magnetic low-voltage lighting

 Electronic low-voltage lighting


 Fluorescent lighting

 LED lighting

 Ceiling fans

 Ceiling fan/lights

Load type requiring load interface

 Neon/cold cathode lighting

Lighting load interfaces may be applicable for some additional load type, voltage, and capacity combinations. For additional information, see pp. 255–259.

Available finishes

Use **BOLD** color code in model number (Example: S-600P-**GR**)

Gloss finishes*



WH
White



LA
Light Almond



AL
Almond



IV
Ivory



GR
Gray



BR
Brown



BL
Black

Metal finish wallplates***



SS
Stainless Steel

* Coordinating wallplates only available separately. For wallplate information, see p. 236.

** Stainless Steel wallplate only available separately and includes black plastic trim/adaptor, visible from side. Match with separate Black (BL) control. For wallplate information, see p. 236

Slide-to-off fan controls



- Slide up to on/increase speed, down to decrease/off
- 3 quiet fan speeds designed to prevent motor hum) for use with only one ceiling paddle fan)
- Fully variable model also available (for use with multiple ceiling paddle or exhaust fans)

Slide-to-off fan/light control with on/off light switch

(two loads)



- Fan control** (top)
 - Slide up to on/increase speed, down to decrease/off
 - 3 quiet fan speeds designed to prevent motor hum (for use with only one ceiling paddle fan)
- Switch** (bottom)
 - Rocker switch turns light on/off

✂ Fan controls

Slide-to-off fan controls—quiet 3-speed

Single-pole SFSQ-F-**XX**¹

120V 1.5A

Single-pole SFSQ-F-HO-**XX**¹

120V 2A

SFSQ-F-HO model for use with Hunter Original Series fans.

No derating required if ganged.

Slide-to-off fan control—fully variable

Single-pole SFS-5E-**XX**¹

120V 5A

Control provides an additional wire for switching of fan light (360W, incandescent/halogen). Light turns on when fan is on, and off when fan is off.

Fully variable fan controls are commonly known as solid state fan controls.

✂ Fan control/light control

Slide-to-off fan/light control—quiet 3-speed with on/off light switch (two loads)

Single-pole SFSQ-LF-**XX**¹

120V 1.5A fan (top)

360W switch (bottom)

Incandescent/halogen

No derating required if ganged.

XX¹: Gloss color codes, see p. 103

Wallplates not included. Order separately, see p. 236

All models must be derated if ganged unless otherwise noted, see pp. 250–252.