





Shown actual size: Skylark dimmer and 1-gang Claro wallplate in White (WH).

Product family features


- Rocker switch returns light to light level indicated by slider on preset dimmers
- Slide up to brighten, down to dim
- C•L® and eco-dim® models available
- Coordinating Claro® and Stainless Steel wallplates only available separately
- Custom engraving available for wallplates, see p. 237

Control types


 Single-pole (one location)


 3-way or 4-way (two or more locations)


Direct load type compatibility


 Incandescent/halogen lighting

 Dimmable CFL/LED lighting (screw-base)


 Magnetic low-voltage lighting

 Electronic low-voltage lighting


 Fluorescent lighting

 LED lighting

 Ceiling fans

 Ceiling fan/lights

Load type requiring load interface

 Neon/cold cathode lighting

Lighting load interfaces may be applicable for some additional load type, voltage, and capacity combinations. For additional information, see pp. 255–259.

Available finishes

Use **BOLD** color code in model number (Example: S-600P-**GR**)

Gloss finishes*



WH
White



LA
Light Almond



AL
Almond



IV
Ivory



GR
Gray



BR
Brown



BL
Black

Metal finish wallplates***



SS
Stainless Steel

* Coordinating wallplates only available separately. For wallplate information, see p. 236.

** Stainless Steel wallplate only available separately and includes black plastic trim/adaptor, visible from side. Match with separate Black (BL) control. For wallplate information, see p. 236

Dual slide-to-off fan/light control

(two loads)



Fan control (left)

- Slide up to on/increase speed, down to decrease/off
- 3 quiet fan speeds designed to prevent motor hum (for use with only one ceiling paddle fan)
- Fully variable model also available (for use with multiple ceiling paddle or exhaust fans)

Dimmer (right)

- Slide up to on/brighten, down to dim/off

✂ Fan/light controls

Dual slide-to-off fan/light control—quiet
3-speed (two loads)

Single-pole	S2-LFSQ- XX ¹
120V 1.5A fan (left)	
300W dimmer (right)	
Incandescent/halogen	

No derating required if ganged.

Dual slide-to-off fan/light control—fully variable
(two loads)

Single-pole	S2-LF- XX ¹
120V 2.5A fan (left)	
300W dimmer (right)	
Incandescent/halogen	

Fully variable fan controls are commonly known as solid state fan controls.

🔩 Replacement knobs

Standard knob	SK- XX ²
Split knobs	contact customer service

XX¹: Gloss color codes, see p. 103

XX²: Available in White (WH), Ivory (IV), Almond (AL) and Light Almond (LA)

Wallplates not included. Order separately, see p. 236

All models must be derated if ganged unless otherwise noted, see pp. 250–252.