Accessories

Wallplates

4.75 in (121 mm)



Shown actual size: 2-gang Claro® wallplate in White (WH). For more information about Designer wallplates, see p. 236.

Coordinated electrical devices



Tamper resistant, selftesting GFCI receptacle



Customizable 6-port frame



Cable jack

For more information about coordinated Designer electrical devices, see p. 237.



Shown actual size: Diva preset dimmer and 1-gang Claro wallplate in White (WH).

Product family features

- Large paddle switch with a captive linear-slide dimmer for a standard designer wallplate opening
- · Preset dimmer
- Select lighter color models feature built-in soft-glow locator light*
- · C·L® and eco-dim® models available
- Coordinating Claro®, Satin Colors®, and Stainless Steel wallplates only available separately
- Custom engraving available for wallplates; see p. 237

Control types

Single-pole (one location)

3-way or 4-way (two or more locations)

Direct load type compatibility

Incandescent/halogen lighting

Dimmable CFL/LED lighting (screw-base)

Magnetic low-voltage lighting

☐ Electronic low-voltage lighting

Fluorescent lighting

LED lighting

Switched lighting/fan/motor

Ceiling fans

Load type requiring load interface

Neon/cold cathode lighting

Lighting load interfaces may be applicable for some additional load type, voltage, and capacity combinations.

For additional information, see pp. 255-259.

^{*} Locator light not available in C·L and 0-10V dimmers, and fan controls

Available finishes

Use **BOLD** color code in model number (Example: DV-600P-**BR**) Gloss finishes*



- * Coordinating wallplates only available separately. For wallplate information, see p. 236.
- ** Stainless Steel wallplate only available separately and includes black plastic trim/adapter, visible from side. Match with separate Black (BL) or Midnight (MN) controls. For wallplate information, see p. 236



(current sink control – power pack required)

Dimmers*

Single-pole DVTV-XX¹ 30 mA max control current Single-pole DVSCTV-**XX**² 30 mA max control current

Control provides dimming signal only. For dimming with on/off switching, use with Lutron Power Pack: PP-DV or PP-347H.

Consult ballast/driver manufacturer for specific ballast/driver current draw to determine maximum number of ballasts/drivers per control.

Compatible with any IEC 60929 Annex E compliant ballast or driver, available from many manufacturers (check for IEC 60929 compliance on the specification of the designed ballast or driver, or confirm compatibility with the manufacturer).

No derating required if ganged.

Dimmers

3-way/single-pole DVFTU-5A3P-XX1 120V 5A DVSCFTU-5A3P-XX2

Also compatible with Advance Mark X ballasts: for further information visit www.lutron.com/advance.

For information on use with Sylvania POWERSENSE ballasts, contact Technical Support at 1.800.523.9466.

XX¹: Gloss color codes, see p. 87 XX²: Satin Colors® codes, see p. 87 Wallplates not included. Order separately, see p. 236

All models must be derated if ganged unless otherwise noted, see pp. 250-252.

*Requires neutral wire connection