





Shown actual size: Diva preset dimmer and 1-gang Claro wallplate in White (WH).









Product family features

- Large paddle switch with a captive linear-slide dimmer for a standard designer wallplate opening
- Preset dimmer
- Select lighter color models feature built-in soft-glow locator light*
- **C•L® and eco-dim® models available**
- Coordinating Claro®, Satin Colors®, and Stainless Steel wallplates only available separately
- Custom engraving available for wallplates; see p. 237


Control types

-  Single-pole (one location)
-  3-way or 4-way (two or more locations)

Direct load type compatibility

-  Incandescent/halogen lighting
-  Dimmable CFL/LED lighting (screw-base)
-  Magnetic low-voltage lighting
-  Electronic low-voltage lighting
-  Fluorescent lighting
-  LED lighting
-  Switched lighting/fan/motor
-  Ceiling fans

Load type requiring load interface

-  Neon/cold cathode lighting

Lighting load interfaces may be applicable for some additional load type, voltage, and capacity combinations.

For additional information, see pp. 255–259.

* Locator light not available in C•L and 0–10V dimmers, and fan controls

Available finishes

Use **BOLD** color code in model number (Example: DV-600P-**BR**)

Gloss finishes*



WH
White



LA
Light Almond



AL
Almond



IV
Ivory



GR
Gray



BR
Brown



BL
Black

Satin Colors® finishes*



SW
Snow



LS
Limestone



BI
Biscuit



ES
Eggshell



PD
Palladium



TP
Taupe



ST
Stone



BG
Bluestone



PL
Plum



SG
Sea Glass



TQ
Turquoise



GS
Goldstone



DS
Desert Stone



GB
Greenbriar

Metal finish wallplate**



MS
Mocha Stone



TC
Terracotta



SI
Sienna



HT
Hot



MR
Merlot



MN
Midnight



SS
Stainless Steel

* Coordinating wallplates only available separately. For wallplate information, see p. 236.

** Stainless Steel wallplate only available separately and includes black plastic trim/adaptor, visible from side. Match with separate Black (BL) or Midnight (MN) controls. For wallplate information, see p. 236

Mechanical switches



- Paddle turns on/off
- Use with any 15A load
- General purpose switching of all light sources and motor loads
- Available with locator light

Fan controls



- Paddle turns on/off
- Slide up to increase speed, down to decrease speed
- 3 quiet fan speeds for increased comfort
- For use with only one ceiling paddle fan
- Does not include locator light
- Designed to prevent motor hum

General purpose switches

Mechanical switches

Single-pole 120/277V 15A	CA-1PS- XX ¹ SC-1PS- XX ²
3-way 120/277V 15A	CA-3PS- XX ¹ SC-3PS- XX ²
4-way 120/277V 15A	CA-4PS- XX ¹ SC-4PS- XX ²

Mechanical switches with locator light

Single-pole 120V 15A	CA-1PSNL- XX ³ SC-1PSNL- XX ⁴
3-way 120V 15A	CA-3PSNL- XX ³ SC-3PSNL- XX ⁴
4-way 120V 15A	CA-4PSNL- XX ³ SC-4PSNL- XX ⁴

Rated for: incandescent/halogen, magnetic low-voltage, electronic low-voltage, fluorescents, CFLs, LEDs, general purpose fans and motor loads.

No derating required if ganged.

Fan controls

Fan controls—quiet 3-speed

3-way/single-pole 120V 1.5A	DVFSQ-F- XX ¹ DVSCFSQ-F- XX ²
3-way/single-pole 120V 2A	DVFSQ-F-HO- XX ¹

DVFSQ-F-HO model for use with Hunter Original Series fans.

Does not include built-in locator light.

No derating required if ganged.

XX¹: Gloss color codes, see p. 87

XX²: Satin Colors® codes, see p. 87

XX³: Only available in Almond (AL), Ivory (IV), Light Almond (LA) and White (WH)

XX⁴: Available in Biscuit (BI), Eggshell (ES), Goldstone (GS), Limestone (LS), Sea Glass (SG) and Snow (SW)

Wallplates not included. Order separately, see p. 236