

Flexible Liquidtight Conduit

Metallic - Coil



Features

- Crush and corrosion resistant steel core for lasting mechanical protection
- EF PVC jacket is oil and sunlight resistant
- Smooth interior for easy wire pull through

Applications

- For use in damp or wet locations, suitable for commercial and industrial use
- Non UL

Standard Material

- EF PVC jacketed steel core coil wrapped in clear plastic shrink wrap

Catalog Number	UPC	Size	Feet Coil	Ship Case	Weight/Case	Inside Diameter		Outside Diameter	
						Min.	Max.	Min.	Max.
6100	80414	3/8"	100'	100'	16	.484	.504	.689	.709
6101	80415	1/2"	100'	100'	26	.622	.642	.819	.839
6102	80417	3/4"	100'	100'	31	.815	.835	1.032	1.051
6103	80419	1"	100'	100'	44	1.032	1.055	1.287	1.315
6104	80421	1-1/4"	50'	50'	46	1.37	1.394	1.63	1.661
6105	80423	1-1/2"	50'	50'	35	1.579	1.598	1.866	1.902
6106	80425	2"	25'	25'	22	2.02	2.043	2.339	2.374
6106C50	86340	2"	50'	50'	49	2.02	2.043	2.339	2.374
6107	80427	2-1/2"	25'	25'	42	2.48	2.504	2.839	2.874
6108	80429	3"	25'	25'	53	3.071	3.102	3.461	3.50
6109	80430	3-1/2"	25'	25'	55	3.50	3.54	3.96	4
6110	80431	4"	25'	25'	57	4	4.039	4.457	4.50