Madison Electric's nipples, elbows and couplings line is an extensive compilation of quality products. Just take a look to see for yourself. All of our UL listed nipples, elbows and couplings meet exacting standards rarely seen in the industry. We give you peace of mind that when you purchase from Madison, you are getting exactly what you need.







NIPPLES, ELBOWS & COUPLINGS

RIGID COUPLINGS

Joins 2 pieces of threaded Rigid/IMC conduit






ITEM#	TRADE SIZE	MIN. LENGTH	MSTR. QTY	ITEM#	TRADE SIZE	MIN. LENGTH	MSTR. QTY
RC-50	1/2"	1-5/8"	100	RC-250	2-1/2"	3-3/16"	24
RC-75	3/4"	1-41/64"	50	RC-300	3"	3-5/16"	16
RC-100	1"	1-31/32"	30	RC-350	3-1/2"	3-13/32"	12
RC-125	1-1/4"	2-1/32"	25	RC-400	4"	3-33/64"	10
RC-150	1-1/2"	2-1/16"	25	RC-500	5"	3-61/64"	1
RC-200	2"	2-1/8"	20	RC-600	6"	4-1/4"	1

SPLIT COUPLINGS MALLEABLE

Joins 2 pieces of threaded Rigid/IMC conduit when conduit is close to a wall, ceiling or other obstruction

Material: Malleable Iron & Neoprene Gasket

Certifications: UL Listed Features: Concrete-tight



RUNNING THREAD

Hangs light duty pendant mount fixtures

Material: Electroplated Steel Certifications: UL Listed

Notes: All items in 3 foot lengths.

Not to be used on conduit for connection at couplings.

ITEM#	TRADE SIZE	MIN. LENGTH	MSTR. QTY	ITEM#	TRADE SIZE	LENGTH	MSTR. QTY
RT-18	1/8"	3,	100	RT-150	1-1/2"	3,	24
RT-14	1/4"	3'	50	RT-200	2"	3'	16
RT-38	3/8"	3'	30	RT-250	2-1/2"	3'	12
RT-50	1/2"	3'	25	RT-300	3"	3'	10
RT-75	3/4"	3'	25	RT-350	3-1/2"	3,	1
RT-100	1"	3'	20	RT-400	4"	3,	1
RT-125	1-1/4"	3'					

RIGID RISERS

Used as a mast support for service entrance applications

Material: Galvanized Steel
Certifications: UL Listed
Features: Threaded on 2 ends
Notes: All items in 7 foot lengths

