

CVTNL1002



Order No.	UPC Bar Code (Qty. 1)	Pipe Size	Diameter (in)	Length (in)	Tap Inlet	Tap Outlet	Ctn. Qty.	Approx. Wt./Lbs.
Ø CVTNL1002	6 42367 41470 2	1"	1.75	3.25	1/8"	1/4"	5	0.95
Ø CVTNL1252	6 42367 41471 9	1-1/4"	2.25	3.87	1/8"	1/4"	5	1.27
Ø CVTNL1502	6 42367 41472 6	1-1/2"	2.50	4.25	1/8"	1/4"	5	1.79
Ø CVTNL2002	6 42367 41473 3	2"	3.12	5.00	1/8"	1/4"	4	2.79

One Tapping on Inlet - One Tapping on Outlet - Custom Tapping Available Upon Request

**No-Lead Bronze Control Center Check Valves**



CVCNL100 Control Center with Pressure Gauge, Brass Nipple, Pressure Switch, Air Valve and Pipe Plug

Order No.	UPC Bar Code (Qty. 1)	Pipe Size	Diameter (in)	Length (in)	Tapping Inlet	Tapping Outlet	Ctn. Qty.	Approx. Wt./Lbs.
Ø CVTNL1003	6 42367 41852 6	1"	1.75	3.25	1/8"	1/8" & 1/4"	5	1.02
Ø CVTNL1253	6 42367 41853 3	1-1/4"	2.25	3.87	1/8"	1/8" & 1/4"	5	1.38
Ø CVCNL100	6 42367 41474 0	1"	1.75	3.25	1/8"	1/8" & (2) 1/4"	5	0.98
Ø CVCNL125	6 42367 41475 7	1-1/4"	2.25	3.75	1/8"	1/8" & (2) 1/4"	5	1.47

Three or Four Tappings - Custom Tapping Available Upon Request

Inlet Side - One 1/8", Outlet Side - One 1/8" and One or Two 1/4"

NOTE: Merrill Manufacutring™ 850 Series and 860 Series check valves are rated for a maximum weight of 300 lbs. in tension (pull down).