

+ 1/4 hp with Form M1

Switch for Pumping Applications

Type FSG & FYG



Order No.	UPC Bar Code (Qty. 1)	Preset Settings (psi)	Cut Out Range (D) psi	Approx. Adjustable Differential (psi)	Approx. Wt./Lbs.
◆ FSG220	7 85901 55924 5	20/40	20-65	15-30	0.85
◆ FSG230	7 85901 07721 3	30/50	20-65	15-30	0.85
◆ FSG240	7 85901 55930 6	40/60	20-65	15-30	0.85
◆ +FSG2M120	7 85901 56237 5	20/40	20-65	15-30	0.90
◆ +FSG2M130	7 85901 20951 5	30/50	20-65	15-30	0.90
◆ *FSG2P20	7 85901 55932 0	20/40	20-65	15-30	0.85
◆ *FSG2P30	7 85901 56109 5	30/50	20-65	15-30	0.85
◆ *FSG2P40	7 85901 56110 1	40/60	20-65	15-30	0.85
◆ •FSG2M420	7 85901 56238 2	20/40	34-65	15-30	0.90
◆ •FSG2M430	7 85901 06618 7	30/50	34-65	15-30	0.90
◆ •FSG2M440	7 85901 45868 5	40/60	34-65	15-30	0.90
◆ FYG220	7 85901 55956 6	20/40	25-80	20-30	0.85
◆ FYG230	7 85901 20958 4	30/50	25-80	20-30	0.85
◆ •FYG2M420	7 85901 96208 3	20/40	39-80	20-30	0.95
◆ •FYG2M430	7 85901 39907 0	30/50	39-80	20-30	0.95

+ Includes Manual Cut-Out Lever - Form M1

* Includes Pulsation Plug - Form P

• Includes Low Pressure Cut-Off - Form M4