

No Hub Pipe Couplings

For joining No Hub cast iron soil pipe.
Sizes 1½" to 15".

Features

Lightweight - Easily installs with standard 60 in./lbs. torque wrench

Adaptability - Longer slots on clamping band readily adapt to varying cast iron pipe diameters

Highly Engineered - A perfect fit when joining hubless cast iron soil pipe and fittings in drain waste and vent applications

Specifications

- Meets and exceeds all material and performance requirements of **ASTM C1277**
- Conforms to **ASTM C564** and **ASTM A240**
- Meets or exceeds all **CISPI® 310** specifications
- All No Hub Couplings use 5/16" hex head screws and tighten to 60 in./lbs. of torque

MISSION TITE® SERVICE WEIGHT GASKETS

For connecting hub and spigot cast iron pipe and fittings.

- Meets **ASTM C564**
- Dual Tite and Extra Heavy Gaskets available on request



Part Number	Pipe Size	Dimensions Width (Inches)
C 150 C	1½"	2.125
C 200 C	2"	2.125
C 215 C	2" x 1½"	2.125
C 300 C	3"	2.125
C 320 C	3" x 2"	2.125
C 400 C	4"	2.125
C 420 C	4" x 2"	2.125
C 430 C	4" x 3"	2.125
C 500 C	5"	3.000
C 600 C	6"	3.000
C 800 C	8"	4.000
C 1000 C	10"	4.000
C 1200 HW	12"	5.500
C 1500 HW	15"	5.500

Part Number	Description
SW 2	2"
SW 3	3"
SW 4	4"
SW 5	5"
SW 6	6"
SW 8	8"
SW 10	10"
SW 12	12"
SW 15	15"

IMPORTANT - Dual Tite and Extra Heavy Gaskets must be ordered in case quantities.