

**ProLine**<sup>®</sup>  
SERIES



Available in lead-free brass, ProLine<sup>®</sup> Push-Fit Fittings provide for simple installations and long-lasting reliability. Compatible with Copper, PEX and CPVC piping, these fittings are certified to NSF 61, IAPMO listed for use in both potable-water and select hydronic-heating applications, and also meet UPC and ICC plumbing code requirements. Their instant, push-fit connections, compact body designs and wide array of fitting types and materials make ProLine<sup>®</sup> Push-Fit Fittings the convenient solution to your joining needs.

A BRAND OF MUELLER INDUSTRIES



PUSH-FIT FITTINGS



## COUPLING DZR LEAD-FREE BRASS

| Item No.        | Size            | Connection | Inner Qty. | Master Qty. | Each Wt. |
|-----------------|-----------------|------------|------------|-------------|----------|
| <b>STANDARD</b> |                 |            |            |             |          |
| 630-001         | 1/4" x 1/4"     | PF x PF    | 60         | 240         | 0.06     |
| 630-002         | 3/8" x 3/8"     | PF x PF    | 50         | 200         | 0.10     |
| 630-003         | 1/2" x 1/2"     | PF x PF    | 40         | 160         | 0.13     |
| 630-004         | 3/4" x 3/4"     | PF x PF    | 30         | 120         | 0.21     |
| 630-005         | 1" x 1"         | PF x PF    | 25         | 100         | 0.34     |
| 630-006         | 1-1/4" x 1-1/4" | PF x PF    | 10         | 40          | 0.89     |
| 630-007         | 1-1/2" x 1-1/2" | PF x PF    | 6          | 24          | 1.44     |
| 630-008         | 2" x 2"         | PF x PF    | 4          | 16          | 2.00     |
| <b>REDUCING</b> |                 |            |            |             |          |
| 630-023         | 3/8" x 1/2"     | PF x PF    | 50         | 200         | 0.12     |
| 630-043         | 3/4" x 1/2"     | PF x PF    | 30         | 120         | 0.18     |
| 630-054         | 1" x 3/4"       | PF x PF    | 25         | 100         | 0.29     |

- Forged dezincification-resistant brass construction
- 316 stainless steel grip ring for strength and corrosion resistance
- Disconnect clip available for removal of fitting
- Dual O-ring design (1-1/4" - 2")
- Integrated brass seal gland
- NSF approved
- Complies with ASSE 1061
- IAPMO listed
- AB1953 compliant
- Full flow design - no tube liners
- Pex stiffeners included with each fitting (1/4" - 1")
- California "Lead-Free" Compliant



630-305

## COUPLING • REPAIR DZR LEAD-FREE BRASS

| Item No.        | Size        | Connection | Inner Qty. | Master Qty. | Each Wt. |
|-----------------|-------------|------------|------------|-------------|----------|
| <b>STANDARD</b> |             |            |            |             |          |
| 630-303         | 1/2" x 1/2" | PF x PF    | 30         | 120         | 0.25     |
| 630-304         | 3/4" x 3/4" | PF x PF    | 20         | 80          | 0.36     |
| 630-305         | 1" x 1"     | PF x PF    | 10         | 40          | 0.51     |

- Forged dezincification-resistant brass construction
- 316 stainless steel grip ring for strength and corrosion resistance
- Disconnect clip available for removal of fitting
- Integrated brass seal gland
- NSF approved
- Complies with ASSE 1061
- IAPMO listed
- AB1953 compliant
- Full flow design - no tube liners
- Pex stiffeners included with each fitting (1/4" - 1")
- California "Lead-Free" Compliant

