



Available in lead-free brass, ProLine[®] Push-Fit Fittings provide for simple installations and long-lasting reliability. Compatible with Copper, PEX and CPVC piping, these fittings are certified to NSF 61, IAPMO listed for use in both potable-water and select hydronic-heating applications, and also meet UPC and ICC plumbing code requirements. Their instant, push-fit connections, compact body designs and wide array of fitting types and materials make ProLine[®] Push-Fit Fittings the convenient solution to your joining needs.



ADAPTER • MALE DZR LEAD-FREE BRASS

Item No.	Size	Connection	Inner Qty.	Master Qty.	Each Wt.
STANDARD					
630-103	1/2" x 1/2"	PF x MPT	40	160	0.12
630-104	3/4" x 3/4"	PF x MPT	30	120	0.19
630-105	1" x 1"	PF x MPT	25	100	0.2
630-106	1-1/4" x 1-1/4"	PF x MPT	10	40	0.72
630-107	1-1/2" x 1-1/2"	PF x MPT	8	32	1.01
630-108	2" x 2"	PF x MPT	8	32	1.41
REDUCING					
630-134	1/2" x 3/4"	PF x MPT	30	120	0.20
630-154	3/4" x 1"	PF x MPT	25	100	0.26

- Forged dezincification-resistant brass construction
- 316 stainless steel grip ring for strength and corrosion resistance
- Disconnect clip available for removal of fitting
- Dual O-ring design (1-1/4" - 2")
- Integrated brass seal gland
- NSF approved
- Complies with ASSE 1061
- IAPMO listed
- AB1953 compliant
- Full flow design - no tube liners
- Pex stiffeners included with each fitting (1/4" - 1")
- California "Lead-Free" Compliant



ADAPTER • FEMALE DZR LEAD-FREE BRASS

Item No.	Size	Connection	Inner Qty.	Master Qty.	Each Wt.
STANDARD					
630-203	1/2" x 1/2"	PF x FPT	40	160	0.13
630-204	3/4" x 3/4"	PF x FPT	30	120	0.20
630-205	1" x 1"	PF x FPT	25	100	0.29
630-206	1-1/4" x 1-1/4"	PF x FPT	10	40	0.74
630-207	1-1/2" x 1-1/2"	PF x FPT	8	32	1.06
630-208	2" x 2"	PF x FPT	8	32	1.47
REDUCING					
630-223	3/8" x 1/2"	PF x FPT	50	200	0.11
630-234	1/2" x 3/4"	PF x FPT	30	120	0.19

- Forged dezincification-resistant brass construction
- 316 stainless steel grip ring for strength and corrosion resistance
- Disconnect clip available for removal of fitting
- Dual O-ring design (1-1/4" - 2")
- Integrated brass seal gland
- NSF approved
- Complies with ASSE 1061
- IAPMO listed
- AB1953 compliant
- Full flow design - no tube liners
- Pex stiffeners included with each fitting (1/4" - 1")
- California "Lead-Free" Compliant

