



Available in lead-free brass, ProLine[®] Push-Fit Fittings provide for simple installations and long-lasting reliability. Compatible with Copper, PEX and CPVC piping, these fittings are certified to NSF 61, IAPMO listed for use in both potable-water and select hydronic-heating applications, and also meet UPC and ICC plumbing code requirements. Their instant, push-fit connections, compact body designs and wide array of fitting types and materials make ProLine[®] Push-Fit Fittings the convenient solution to your joining needs.



90° ELBOW • THREADED DZR LEAD-FREE BRASS

Item No.	Size	Connection	Inner Qty.	Master Qty.	Each Wt.
MPT					
631-203	1/2" x 1/2"	PF x MPT	40	160	0.18
FPT					
631-303	1/2" x 1/2"	PF x FPT	40	160	0.19

- Forged dezincification-resistant brass construction
- 316 stainless steel grip ring for strength and corrosion resistance
- Disconnect clip available for removal of fitting
- Integrated brass seal gland
- NSF approved

- Complies with ASSE 1061
- IAPMO listed
- AB1953 compliant
- Full flow design - no tube liners
- Pex stiffeners included with each fitting (1/4" - 1")
- California "Lead-Free" Compliant



TEE DZR LEAD FREE BRASS

Item No.	Size	Connection	Inner Qty.	Master Qty.	Each Wt.
STANDARD					
632-001	1/4" x 1/4" x 1/4"	PF x PF x PF	40	160	0.09
632-002	3/8" x 3/8" x 3/8"	PF x PF x PF	30	120	0.16
632-003	1/2" x 1/2" x 1/2"	PF x PF x PF	30	120	0.24
632-004	3/4" x 3/4" x 3/4"	PF x PF x PF	20	80	0.39
632-005	1" x 1" x 1"	PF x PF x PF	10	40	0.64
632-006	1-1/4" x 1-1/4" x 1-1/4"	PF x PF x PF	6	24	1.59
632-007	1-1/2" x 1-1/2" x 1-1/2"	PF x PF x PF	4	16	2.53
632-008	2" x 2" x 2"	PF x PF x PF	4	16	3.69
REDUCING					
632-433	3/4" x 1/2" x 1/2"	PF x PF x PF	20	80	0.28
632-434	3/4" x 1/2" x 3/4"	PF x PF x PF	20	80	0.34
632-443	3/4" x 3/4" x 1/2"	PF x PF x PF	20	80	0.32
632-554	1" x 1" x 3/4"	PF x PF x PF	15	60	0.53

- Forged dezincification-resistant brass construction
- 316 stainless steel grip ring for strength and corrosion resistance
- Disconnect clip available for removal of fitting
- Dual O-ring design (1-1/4" - 2")
- Integrated brass seal gland

- NSF approved
- Complies with ASSE 1061
- IAPMO listed
- AB1953 compliant
- Full flow design - no tube liners
- Pex stiffeners included with each fitting (1/4" - 1")
- California "Lead-Free" Compliant

