

ProLine[®]
SERIES



Available in lead-free brass, ProLine[®] Push-Fit Fittings provide for simple installations and long-lasting reliability. Compatible with Copper, PEX and CPVC piping, these fittings are certified to NSF 61, IAPMO listed for use in both potable-water and select hydronic-heating applications, and also meet UPC and ICC plumbing code requirements. Their instant, push-fit connections, compact body designs and wide array of fitting types and materials make ProLine[®] Push-Fit Fittings the convenient solution to your joining needs.

A BRAND OF MUELLER INDUSTRIES



PUSH-FIT FITTINGS



Push-Fit Fittings



CAP DZR LEAD-FREE BRASS

Item No.	Size	Connection	Inner Qty.	Master Qty.	Each Wt.
STANDARD					
633-001	1/4"	PF	60	240	0.03
633-002	3/8"	PF	50	200	0.05
633-003	1/2"	PF	50	200	0.08
633-004	3/4"	PF	40	160	0.13
633-005	1"	PF	25	100	0.20
633-006	1-1/4"	PF	12	48	0.49
633-007	1-1/2"	PF	8	32	0.80
633-008	2"	PF	6	24	1.13

- Forged dezincification-resistant brass construction
- 316 stainless steel grip ring for strength and corrosion resistance
- Disconnect clip available for removal of fitting
- Dual O-ring design (1-1/4" - 2")
- Integrated brass seal gland
- NSF approved
- Complies with ASSE 1061
- IAPMO listed
- AB1953 compliant
- Full flow design - no tube liners
- Pex stiffeners included with each fitting (1/4" - 1")
- California "Lead-Free" Compliant



DISCONNECT CLIP PLASTIC / STAINLESS STEEL

Item No.	Size	Connection	Inner Qty.	Master Qty.	Each Wt.
PLASTIC					
636-001	1/4"	NA	100	400	0.01
636-002	3/8"	NA	100	400	0.01
636-003	1/2"	NA	100	400	0.01
636-004	3/4"	NA	100	400	0.02
636-005	1"	NA	100	400	0.02
STAINLESS STEEL					
636-006	1-1/4"	NA	10	40	0.19
636-007	1-1/2"	NA	10	40	0.20
636-009	2"	NA	10	40	0.03

- Disconnect clip for removal of fitting
- Durable plastic construction (1/4" - 1")
- Disconnect clip for removal of fitting
- Stainless steel construction (1-1/4" - 2")