



90° ELBOW DZR LEAD-FREE BRASS

Item No.	Size	Connection	Inner Qty.	Master Qty.	Each Wt.
STANDARD					
631-001	1/4" x 1/4"	PF x PF	60	240	0.07
631-002	3/8" x 3/8"	PF x PF	40	160	0.12
631-003	1/2" x 1/2"	PF x PF	40	160	0.17
631-004	3/4" x 3/4"	PF x PF	25	100	0.31
631-005	1" x 1"	PF x PF	15	60	0.48
631-006	1-1/4" x 1-1/4"	PF x PF	8	32	1.16
631-007	1-1/2" x 1-1/2"	PF x PF	6	24	1.84
631-008	2" x 2"	PF x PF	6	24	2.79
REDUCING					
631-043	3/4" x 1/2"	PF x PF	25	100	0.21
631-054	1" x 3/4"	PF x PF	15	60	0.37

- Forged dezincification-resistant brass construction
- 316 stainless steel grip ring for strength and corrosion resistance
- Disconnect clip available for removal of fitting
- Dual O-ring design (1-1/4" - 2")
- Integrated brass seal gland
- Certified to NSF 61-G

- Complies with ASSE 1061
- IAPMO listed
- AB1953 compliant
- Full flow design - no tube liners
- Pex stiffeners included with each fitting (1/4" - 1")
- "Lead-Free" Compliant



90° ELBOW • DROP EAR DZR LEAD-FREE BRASS

Item No.	Size	Connection	Inner Qty.	Master Qty.	Each Wt.
STANDARD					
631-103	1/2" x 1/2"	PF x FPT	40	160	0.23
REDUCING					
631-123	3/8" x 1/2"	PF x FPT	40	160	0.19

- Forged dezincification-resistant brass construction
- 316 stainless steel grip ring for strength and corrosion resistance
- Disconnect clip available for removal of fitting
- Integrated brass seal gland
- Certified to NSF 61-G

- Complies with ASSE 1061
- IAPMO listed
- AB1953 compliant
- Full flow design - no tube liners
- Pex stiffeners included with each fitting
- "Lead-Free" Compliant

