



- ▶ Touch Proof Recessed Screws and Tubular Contacts provide added safety and helps prevent short circuits
- ▶ Tubular Contacts connect stripped, un-terminated solid or stranded wire directly to each contact
- ▶ Integrated Stainless Steel Spring Wire Protectors prevent twisting and breakage of stranded wire during termination
- ▶ Modular 12-Circuit Design can be cut into smaller sections, or stacked end-to-end
- ▶ Dead Front Design to prevent shorts
- ▶ Rugged Nylon 66 Housing, UL 94V2
- ▶ Operating temperature rated at 230°F(110°C)
- ▶ Brass Metal Alloy, Nickel Plated Terminal Insert
- ▶ Zinc Plated, yellow chromated screws
- ▶ Can be used for AC & DC Applications
- ▶ 300V
- ▶ 221°F(105°C)

Dimensions = Inches

Cat No.	Amp	Volts	Wire Range	A	B	C	D	E	F	Strip Length	Bag Qty
Header Card - 2 Pack											
22152	20	300	22-12	3.79	.669	.570	.315	.114	.110	.20	2
22154	30	300	22-10 Sol 22-12 Str	4.62	.795	.670	.394	.142	.134	.25	2
22156	35	300	22-10	5.54	.937	.748	.472	.154	.154	.27	2
22158	50	300	20-8	6.22	1.008	.992	.531	.173	.189	.35	2
Bag - 50 Pack											
22052	20	300	22-12	3.79	.669	.570	.315	.114	.110	.20	50
22054	30	300	22-10 Sol 22-12 Str	4.62	.795	.670	.394	.142	.134	.25	50
22056	30	300	22-10	5.54	.937	.748	.472	.154	.154	.27	40
22058	50	300	20-8	6.22	1.008	.992	.531	.173	.189	.35	25