

# 6" LINE VOLTAGE HOUSINGS MEDIUM BASE

A19 / R/PAR20 / R/PAR30 / R40/PAR38 · IC AND NON-IC

All Nora 6" housings are thermally protected, listed for damp location, and include an adjustable socket, 24-1/2" adjustable bar hangers with captive nails and quick connector. Trim determines maximum wattage.



## NFBIC-6INCAT\*

6" 2-Hour Fire Rated Line Volt Housing  
Dia: 4-3/8" Depth: 6-3/8"



## NHIC-17/100DWQA

A19 / BR/PAR30 / BR40/PAR38

6" IC Airtight Line Voltage Housing  
Dia: 6-3/8" Depth: 7-3/4"



## NHIC-17QAT

NHIC-17QNBAT **NB** Floating Socket

A19 / R/PAR20 / BR/PAR30 / BR40/PAR38

6" IC Airtight Line Voltage Housing  
Dia: 6-3/8" Depth: 7-1/2"



## NHRIC-17QAT

NHRIC-17QNBAT **NB** Floating Socket

A19 / R/PAR20 / BR/PAR30 / BR40/PAR38

6" IC Airtight Line Voltage Remodel  
Dia: 6-3/8" Depth: 7-1/2"



NHIC-27QAT **SH** A19 / R/PAR20 / BR/PAR30

6" IC AT Line Volt. Shallow Housing

Dia: 6-3/8" Depth: 5-1/2"

NHRIC-27QAT **SH** A19 / R/PAR20 / BR/PAR30

6" IC AT Line Volt. Shallow Remodel

Dia: 6-3/8" Depth: 5-1/2"



## NH-26Q

NH-26QNB **NB** Floating Socket

A19 / R/PAR20 / BR/PAR30 / BR40/PAR38

6" Non-IC Line Voltage Housing  
Dia: 6-3/8" Depth: 7-1/2"



## NHR-26Q

A19 / R/PAR20 / BR/PAR30 / BR40/PAR38

6" Non-IC Line Voltage Remodel  
Dia: 6-3/8" Depth: 7-1/2"

NH-27Q **SH** A19 / R/PAR20 / BR/PAR30

6" Non-IC Line Volt. Shallow Housing

Dia: 6-3/8" Depth: 5-1/2"

NHR-27Q **SH** A19 / R/PAR20 / BR/PAR30

6" Non-IC Line Volt. Shallow Remodel

Dia: 6-3/8" Depth: 5-1/2"

Nora Lighting will label with Reduced Maximum Wattage - add "/wattage".  
Example **NHIC-17QAT/25** - Wattage is 25W max

**NB** No Bracket-Floating Socket **SH** Shallow **CC** Custom Combinations **■** Airtight