

24V LED LIGHTBAR ACCESSORIES

LED LIGHTBAR 90+ AND LIGHTBAR PRO 90+



Power Line Interconnector
NAL-208 20" Cable
NAL-208/72 72" Cable
NAL-212 12" w/ Switch



90° Power Line Interconnector
NAL-207 20" Cable
NAL-207/72 72" Cable



Mini Power Feed Splitter
NAL-221
 One in and four out



*Flexible Extension Cord
NRA-125/6 6" Cable
NRA-125/12 12" Cable
NRA-125/18 18" Cable
NRA-125/72 72" Cable
 Use with NATL-530HW,560HW
 to connect to NUSP-Jbox



Flexible Power Cord
NRA-6035W/6 6'
NRA-6035W/10 10'
 use with NATL-530HW,560HW



Mini Coupler
NAL-220



NEW!
 Dimmable Class II Remote
 Hardwire Magnetic Driver
 with Integral Regulator for
 Constant Current & Voltage
NMTD-60/24D* 60W
NMTD-96/24D* 96W
 Includes NALTL-10 · 120/277V input



Dimmable Class II Remote
 Hardwire Magnetic Driver
 with Integral Regulator for
 Constant Current and Voltage
NMT-303/24C2D1*†
 3x100W
 Includes (3) NALTL-10



Hardwired Class II
 Electronic Driver
NATL-530HW* 30W
NATL-560HW* 60W
 Requires NUSP-JBox or
 NRA-6035



Class II Electronic LED
 Driver
NATL-5060HW* 60W
NATL-5100HW* 100W
 Includes NALTL-10



Plug-In Electronic Driver
NATL-524* 24W 24V DC
NATL-545* 45W 24V DC
NATL-596* 96W 24V DC



Power Line Connector
NALTL-10 10' Cable
NALTL-30 30' Cable
NATL-302 5" Splitter



Low Voltage Splice Box
NATL-415W



Junction Box for Hard
 Wiring
NUSP-JBox



Dimmer
NAL-250

*Requires power line interconnector to power lightbar unless using NAL-230 or NAL-255.
 Due to unknown ambient temperatures, Nora recommends de-rating drivers by 20%

12V & 24V LED TAPE LIGHT STANDARD & SIDE-LIT ACCESSORIES



Junction Box for Hard Wiring
NUSP-JBox



Low Voltage Splice Box
NATL-415W



Plug-In Electronic Driver
NAPK-524/12 12W 24V DC
NATL-524 24W 24V DC
NATL-545 45W 24V DC
Requires power line interconnector



Class II Electronic LED Driver
NATL-550/12 12V 50W
NATL-596 24V 96W



Class II Electronic LED Driver (Non Dimmable)
NATL-5060HW 24V 60W
NATL-5100HW 24V 100W
Includes hardwire box and NALTL-10 power line connector



Hardwired Class II Electronic Driver
NAPK-530HW/12 12V 30W
NAPK-560HW/12 12V 30W
NATL-530HW 24V 30W
NATL-560HW 24V 60W
Requires NUSP-JBox or NRA-6035 and power line interconnector



24V Dimmable Class II Remote Hardwire Magnetic Driver with Integral Regulator for Constant Current and Voltage 120/277V input
NMT-303/24C2D1 3x100W
NMTD-60/24D 60W
NMTD-96/24D 96W
Includes NALTL-10 Power Line Connector



12V Dimmable Class II Hardwire Magnetic Driver with Integral Regulator for Constant Current and Voltage
NMT-244/12C2D1 4x60W
NMTD-40/12D 40W
NMTD-60/12D 60W
Includes NAPK-10 Power Line Connector



In-Line Dimmer
NATL-518 212V & 24V
60W Max (12V)
120W Max (24V)

Due to unknown ambient temperatures, Nora recommends de-rating drivers by 20%.

24V LED TAPE LIGHT HY-BRITE & HIGH OUTPUT DRIVERS



Hardwired Class II
Electronic Driver
NATL-530HW 30W
NATL-560HW 60W
Requires NUSP-JBox or
NRA-6035 and power line
interconnector



Plug-In Electronic Driver
NATL-524 24W
NATL-545 45W
Requires NUSP-JBox or
NRA-6035



Class II Electronic LED
Driver
NATL-596 24V 96W



Class II Electronic LED
Driver (Non Dimmable)
NATL-5060HW 24V 60W
NATL-5100HW 24V 100W
Includes NALTL-10 power
line connector



Dimmable Class II Remote
Hardwire Magnetic Driver
with Integral Regulator for
Constant Current and Voltage
120/277V Input
NMTD-60/24D* 60W
NMTD-96/24D* 96W
Includes NALTL-10 Power
Line Connector



Dimmable Class II
Hardwire Magnetic Driver
with Integral Regulator for
Constant Current and Voltage
NMT-303/24C2D1 3x100W
Includes (3) NALTL-10 Power
Line Connectors

Due to unknown ambient temperatures, Nora recommends de-rating drivers by 20%.



12V & 24V RGB LED TAPE LIGHT & 24V CCT TAPE LIGHT ACCESSORIES



RGB 2.4G RF Controller
NARGB-860 Controller
NARGB-861 Remote-90'
12V or 24V, 7 state colors
or 15 changing modes.
Synchronize up to 4 controllers.



RGB Wall Controller
NARGB-866
12V - 144W or 24V - 288W max
7state colors or 4 changing
modes.



CCT Color Tuning
(25K-45K) Controller
NACCT-865 Controller
NACCT-867 Remote
Both controller and remote are
required.



Hand Held Remote
NARGB-761
for use with NARGB-760
and NARGB-765



RGB Controller
NARGB-760 24V
NARGB-765 12V



Controller Power Line
Connector
NATL-511 24V, 11"
NATL-517 12V, 11"



Class II Electronic LED
Driver
NATL-550/12 12V 50W
NATL-596 24V 96W



Plug-In Electronic Driver
NAPK-524/12 12W 24V DC
NATL-524 24W 24V DC
NATL-545 45W 24V DC
Requires NUSP-JBox or
NRA-6035



Class II Electronic LED
Driver
NATL-5060HW 24V 60W
NATL-5100HW 24V 100W
Includes hardwire box
and NATL-10 power line
connector



Hardwired Class II
Electronic Driver
NAPK-530HW/12 12V 30W
NAPK-560HW/12 12V 60W
NATL-530HW 24V 30W
NATL-560HW 24V 60W
Requires NUSP-JBox or
NRA-6035



12V Class II Hardwire
Magnetic Driver
NMT-244/12C2D1 4x60W
NMTD-40/12D* 40W
NMTD-60/12D* 60W
Includes NATL-10 Power
Line Connector



24V Class II Hardwire
Magnetic Driver
NMT-303/24DC2D1 3x100W
NMTD-60/24D* 60W
NMTD-96/24D* 96W
Includes NATL-10 Power
Line Connector

* 120/277V Input

Due to unknown ambient temperatures, Nora recommends de-rating drivers by 20%.

24V LED TAPE LIGHT RGBW COLOR CHANGE ACCESSORIES



NEW!
RGBW RF Controller
NARGBW-965
for use with remote
NARGBW-967



NEW!
RGBW RF Remote
NARGBW-967
90' max distance from
controller



Controller Power Line
Connector
NARGBW-962 10'
NARGBW-963 30'



Class II Electronic LED
Driver
NATL-596 24V 96W



Plug-In Electronic Driver
NAPK-524/12 12W 24V DC
NATL-524 24W 24V DC
NATL-545 45W 24V DC
Requires NUSP-JBox or
NRA-6035



Class II Electronic LED
Driver
NATL-5060HW 24V 60W
NATL-5100HW 24V 100W
Includes hardwire box
and NATL-10 power line
connector



Hardwired Class II
Electronic Driver
NATL-530HW 24V 30W
NATL-560HW 24V 60W
Requires NUSP-JBox or
NRA-6035



NEW!
24V Class II Hardwire
Magnetic Driver
NMT-303/24DC2D1 3X100W
NMTD-60/24D* 60W
NMTD-96/24D* 96W
Includes NATL-10 Power
Line Connector
* 120/277V Input



NEW!
In-Line Dimmer
NATL-518 212V & 24V
60W Max (12V)
120W Max (24V)