

12V & 24V LED TAPE LIGHT STANDARD & SIDE-LIT ACCESSORIES



Shrink Wrap Tubes
NATL-400 Pack of 5



Mounting Clips
NATL-401 Pack of 5



4' Channel
NATL-420 Plastic B/W



4' Aluminum Channel w/Lens
NATL-C23 Shallow Wings
NATL-C24 Shallow



4' Aluminum Channel w/Lens
NATL-C25 Deep Wings
NATL-C26 Deep



4' Aluminum Channels
NATL-C27 J-Style
NATL-C28 Corner w/Lens



End Cap
NATL-403 12V / 24V



Power Line Interconnector
NATL-509 24V, 9"
NATL-515 12V, 9"



Power Line Interconnector with Switch
NATL-511 24V, 11"
NATL-517 12V, 11"



12V / 24V Interconnection Cables
NATL-202 2" Cable
NATL-206 6" Cable
NATL-218 18" Cable
NATL-236 36" Cable
NATL-272 72" Cable



12V / 24V Splitter Cable
NATL-300 "Y" Cable



12V / 24V Splitter Cable
NATL-301 "X" Cable



Power Line Connector
NAPK-10 12V, 10'
NAPK-30 12V, 30'
NALTL-10 24V, 10'
NALTL-30 24V, 30'



Flexible Extension Cord
NRA-125/6 6" Cable
NRA-125/12 12" Cable
NRA-125/18 18" Cable
NRA-125/72 72" Cable



Flexible Power Cord
NRA-6035W/6 6'
NRA-6035W/10 10'

NEW! **NATL-302** 24V 5" Splitter

Use with NATL-530HW, 560HW to connect to NUSP-Jbox

12V & 24V RGB LED TAPE LIGHT & 24V CCT TAPE LIGHT ACCESSORIES



RGB 2.4G RF Controller
NARGB-860 Controller
NARGB-861 Remote-90'
12V or 24V, 7 state colors
or 15 changing modes.
Synchronize up to 4 controllers.



RGB Wall Controller
NARGB-866
12V - 144W or 24V - 288W max
7state colors or 4 changing
modes.



CCT Color Tuning
(25K-45K) Controller
NACCT-865 Controller
NACCT-867 Remote
Both controller and remote are
required.



Hand Held Remote
NARGB-761
for use with NARGB-760
and NARGB-765



RGB Controller
NARGB-760 24V
NARGB-765 12V



Controller Power Line
Connector
NATL-511 24V, 11"
NATL-517 12V, 11"



Class II Electronic LED
Driver
NATL-550/12 12V 50W
NATL-596 24V 96W



Plug-In Electronic Driver
NAPK-524/12 12W 24V DC
NATL-524 24W 24V DC
NATL-545 45W 24V DC
Requires NUSP-JBox or
NRA-6035



Class II Electronic LED
Driver
NATL-5060HW 24V 60W
NATL-5100HW 24V 100W
Includes hardwire box
and NATL-10 power line
connector



Hardwired Class II
Electronic Driver
NAPK-530HW/12 12V 30W
NAPK-560HW/12 12V 60W
NATL-530HW 24V 30W
NATL-560HW 24V 60W
Requires NUSP-JBox or
NRA-6035



12V Class II Hardwire
Magnetic Driver
NMT-244/12C2D1 4x60W
NMTD-40/12D* 40W
NMTD-60/12D* 60W
Includes NATL-10 Power
Line Connector



24V Class II Hardwire
Magnetic Driver
NMT-303/24DC2D1 3x100W
NMTD-60/24D* 60W
NMTD-96/24D* 96W
Includes NATL-10 Power
Line Connector

* 120/277V Input

Due to unknown ambient temperatures, Nora recommends de-rating drivers by 20%.