

PATENT
PENDING

LED IOLITE SERIES

4" RETROFIT TRIMS 800 LUMEN

MODULAR ADJUSTABLE LED DOWNLIGHT

4" Iolite retrofit allows the complete family of 4" die-cast aluminum trims to be used as 4" adjustable accent or downlights in existing 4" Nora housings or housing by others.

FEATURES:

- 4" aperture
- 800 Lumens
- High color rendition - CRI 95
- 2700K, 3000K, and 4000K color temperatures
- 60° beam spread installed with 25° and 38° reflectors included with each module.
- 15° reflector available
- Dimmable - 120V TRIAC
- Cree LED COB package
- 4 finishes including matte powder white
- 5-year limited warranty
- cULus and Energy Star listed for wet location

Note: Includes male connector for hard wiring. (removing existing socket)

Square Cone Regress
NIR-4SC
BZ, BW, HW,
MPW, NN, WW

Dimension

H: 5.75" W: 4.93"
Aperture: 3.31"



Medium Screw Base (included)

Optional GU24 adapter available



5 YEAR
LIMITED WARRANTY

4" IOLITE RETROFIT SERIES REFLECTORS

SERIES	SIZE	SHAPE	STYLE	TEMP	SPREAD	FINISH / FLANGE
NIR- Iolite Ret- rofit	4 4"	R Round	G Surface Regress	27 2700K	X 25°/38° /60°	BW* Black / White BZ Bronze / Bronze HW* Haze / White MPW Matte Powder White NN Natural Metal WW White / White <i>*Finish not available on Surface Regress</i>
			S Cone Regress	30 3000K		
			C Cone Regress	40 4000K		

4" IOLITE RETROFIT SERIES FINISHES (Not all finishes available on all trims)

Example: **NRI-4RC27XWW** - 4" Iolite Retrofit Series Round Cone Regress Dedicated Trim with Module, 800 Lumen, 2700K, White with White

COMPATIBLE HOUSINGS for Iolite Retrofit

- New Construction
NHIC-4G24AT 4" ICAT GU24[†]
NHIC-4LMARAT 4" ICAT Dedicated LED
NHIC-4LMARAT/277 4" ICAT Dedicated LED, 277

Remodel

- NSRIC-404QAT** 4" Remodel AT Line Voltage
NHRIC-4LMRAT/277 4" ICAT Dedicated LED, 277

Fire Box

- NFBIC-4INCAT** 4" ICAT Fire Box
NFBIC-4LMRAT 4" ICAT Dedicated LED Fire Box

2" & 4" IOLITE ACCESSORIES

- NIO-2HC** Hex Cell louver for 2" & 4"
NIO-REFL15FR 15° Reflector w/Frosted lens
NIO-REFL25FR 25° Reflector w/Frosted lens
NIO-REFL38FR 38° Reflector w/Frosted lens
NIO-REFL60FR 60° Reflector w/Frosted lens

[†]Requires NRA-212SM - GU24 adaptor

