

NUTP1 Series (Amber Finish)

NUTP1-W Series (White Finish) 24V Standard LED Tape Light Roll

Source: 24W - 1.5 Watts Per Foot

PRODUCT DESCRIPTION

LED Tape Light is a perfect solution for your LED linear lighting needs. This energy efficient and very low profile LED Tape is great for use in cove lighting, architectural enhancements, under cabinet or many more discreet locations. This flexible LED light source is a durable silicone encapsulated tape, cULus Listed for Wet Location applications and IP65 rated. Available in a roll, kit, or sections. Each roll or kit comes with (16) 12" sections linked together.

FEATURES

- 70 lumens per foot with 3000K CCT
- 288 LEDs / 24W per roll; 18 LEDs / 1.5W per foot
- 12V or 24V DC single color illumination
- Available in 90+ CRI
- Maximum run: Electronic Driver (24V) 66' with 100W driver, (12V) 40' with 60W driver
- Separable every 12", easily disconnected and connected without soldering
- Field cuttable every 2" on 12V and 4" on 24V
- Easy to install; pre-applied 3M™ tape or 15 acrylic mounting clips (included with roll/kit)
- Available Colors: Blue, Green, Red, Yellow, 2700K, 3000K, 4200K
- cULus Listed for Wet Location and IP65 rated
- Exceeds Title 24 high efficacy requirements
- No soldering or additional wiring is required
- No flicker delay or warm up like compact fluorescent products
- No UV light or infrared wavelengths
- 3 Year Limited Warranty
- Dimmable with dimmable power supply

CONSTRUCTION

The silicone encapsulated tape can be cut every 6 LEDs at marked intervals. Cutting does not effect circuit (shrink wrap tube included for concealment). LED Tape Light is also separable every 12", each connection has pre-installed shrink wrap around power connections to ensure wet location listing. Simply slice the clear shrink wrap at each electrical connection, and separate pieces. This eliminates soldering when using partial rolls. Each roll or kit comes with 12" power line connector NATL-509.

MOUNTING

Each Tape Light roll or kit comes with 15 clear acrylic clips and also comes with pre-applied 3M™ adhesive tape for simple installation. An optional aluminum channel is available.

ELECTRICAL

Power: 24 Volt DC Input / 1.5 Watts Per Foot / 24 Watts Per Roll

Light Source: 18 LEDs Per Foot / 288 LEDs Per Roll

Operating Temperature: -25°C ~ 60°C (-13°F ~ 140°F)

Life Expectancy: 50,000 Hours

Maximum Run Length: 66' (w/ NATL-5100)

Color Temperature: Blue, Green, Red, Yellow, Cool White (4200K), Warm White (3000K), Warm White (2700K)

TAPE LIGHT KIT (NUTP1-16LED30PS)

Tape Light Kit is a complete package ready from the box. Includes: 16' 3000K Tape Light Roll [NUTP1-16LED30], (15) acrylic mounting clips with screws, (1) 12" power line interconnector [NATL-509], (5) Shrink Wrap Tubes [NATL-400], and (1) 24W Plug-In Driver [NATL-524]

DIMMABLE

There may be some cases that require more than one lighting fixture to be used to meet minimum dimmer load. Consult with dimmer manufacturer. [Click Here](#) or refer to www.NoraLighting.com for complete updated dimmer list in the "Compatibility" page under the "Resource" tab.

LABELS AND LISTINGS

cULus Listed for Wet Location¹ (not submersible)


IP65 Rated

California Energy Commission

3 Year Limited Warranty



DIMENSIONS



HARDWARE DRIVERS

NAPK-530HW/12: 12V DC / 30W Class II Hardwired LED Driver

NAPK-560HW/12: 12V DC / 60W Class II Hardwired LED Driver

NAPK-530HW: 24V DC / 30W Class II Hardwired LED Driver

NAPK-560HW: 24V DC / 60W Class II Hardwired LED Driver

PLUG-IN DRIVERS

NAPK-524/12: 12V DC / 24W Direct Plug-In LED Driver

NATL-524: 24V DC / 24W Direct Plug-In LED Driver

NATL-545: 24V DC / 45W Direct Plug-In LED Driver

NATL-550/12: 12V DC / 50W Direct Plug-In LED Driver

NATL-596: 24V DC / 96W Direct Plug-In LED Driver

DRIVER ACCESSORIES

NRA-125/6: 6' Extension Cord for NAPK-530HW/12 & NAPK-560HW/12

NRA-125/12: 12' Extension Cord for NAPK-530HW/12 & NATL-560HW/12

NRA-125/18: 18' Extension Cord for NAPK-530HW/12 & NATL-560HW/12

NRA-125/72: 72' Extension Cord for NAPK-530HW/12 & NATL-560HW/12

NRA-6035W/6: 6' Cord and Plug for NAPK-530HW/12 & NATL-560HW/12

NRA-6035W/10: 10' Cord and Plug for NAPK-530HW/12 & NATL-560HW/12

NUSP-JBox: Junction Box required for hardwiring NAPK-530HW/12 & NATL-560HW/12

TAPE LIGHT ACCESSORIES

NATL-2xx: Interconnection Cable (available in 2", 6", 18", 36", 72")

NATL-300: "Y" Splitter Cable

NATL-301: "X" Splitter Cable

NATL-400: Shrink Wrap Tube (Pack of 5)

NATL-401: Clear Acrylic Mounting Clips (Pack of 15)

NATL-403: End Cap

NATL-420: 4' Plastic Channel (Black or White)

NATL-515: 9" Power Line Interconnector

NATL-517: 11" Power Line Interconnector with Switch

NATL-C23: 4" Aluminum Channel, Shallow w/ Wings

NATL-C24: 4" Aluminum Channel, Shallow

NATL-C25: 4" Aluminum Channel, Deep w/ Wings

NATL-C26: 4" Aluminum Channel, Deep

NATL-C27: 4" Aluminum Channel, J-Style

NATL-C28: 4" Aluminum Channel, Corner

NATL-518: In-Line Dimmer (12V & 24V, 72W Max)

AMBER FINISH

Item No.	LED Length	Color	Section
NUTP1-	16 LED = 16' Roll	B = Blue G = Green R = Red Y = Yellow 27 = 2700K 30 = 3000K 42 = 4200K	/12 = 12"
	LED = 12" or 4" Section		/4 = 4"

WHITE FINISH 90+ CRI

Item No.	LED Length	CRI	Color Temp	Section
NUTP1-W	16 LED = 16' Roll	9 = 90+ CRI	27 = 2700K	/12 = 12"
	LED = 12" or 4" Section		30 = 3000K	
			42 = 4200K	

¹ To maintain wet location when connecting 2 sections; add clear shrink wrap over mating pieces and shrink wrap per instructions. Shrink wrap tubes are included with each roll (5) and section (2)

Create a complete fixture / driver catalog number: Example: NUTP1-16LED27/12