

POLARIS™ INSULATED CONNECTORS
Multi-Conductor Connector
Either Side Wire Entry
IPLD SERIES



FEATURES

- Wire entry ports on both sides of the connector allow for access from either side.
- Eliminates the need for cover and taping.
- Insulated with high-dielectric strength plastisol.
- Molded for precise fit and supplied with removable access plugs over the hex screws.
- Supplied with removable plugs to close the entry port not being utilized.
- Abrasion and chemical resistant, UV resistant.
- Will not support combustion.

RATINGS



UL Listed 486B Wire Connector.

TEMPERATURE RATING/VOLTAGE:

AL9CU. Cold temperature rated to -45 °C, rated 600V, 90 °C.

WIRE TYPE:

Dual rated for use with copper and/or aluminum cables. Not recommended for fine-stranded, flexible wire.

All dimensional data is listed in inches.

CAT. NO.	NO. OF PORTS
IPLD3/0-3	3
IPLD3/0-4	4
IPLD3/0-5	5
IPLD3/0-6	6
IPLD3/0-7	7
IPLD3/0-8	8
IPLD3/0-10	10
IPLD3/0-12	12
IPLD250-3	3
IPLD250-4	4
IPLD250-5	5
IPLD250-6	6
IPLD250-7	7
IPLD250-8	8
IPLD250-10	10
IPLD250-12	12
IPLD350-3	3
IPLD350-4	4
IPLD350-5	5
IPLD350-6	6
IPLD350-7	7
IPLD350-8	8
IPLD350-9	9
IPLD350-10	10
IPLD350-12	12