



WALL CAPS




Model WC638

- For 3¼" x 14" duct
- Spring-loaded backdraft damper and bird screen
- 26 GA CRCQ Steel, black finish



Model 639

- For 31/4" x 10" duct
- Spring-loaded backdraft damper and bird screen
- 24 GA CRCQ Steel, black electrically-bonded epoxy finish
- Do not use for dryer venting




Model 649

- Same features as Model 639
- .025 Aluminum natural finish


Model 647

- For 7" round duct
- Spring-loaded backdraft damper and bird screen
- .025 Aluminum natural finish
- Do not use for dryer venting



Model 843BL

- For 6" round duct
- Spring-loaded backdraft damper and bird screen
- 22 GA CRCQ Steel, black electrically-bonded epoxy finish
- Attachment collar 1¼" long
- Do not use for dryer venting



Model 641


- Same features as Model 843BL
- .025 Aluminum natural finish

Model 641FA

- Same features as Model 641
- Without backdraft damper
- Intended for make-up air inlet applications


Model 885BL

- For 3" or 4" round duct (4" to 3" transition included)
- Spring-loaded backdraft damper and bird screen
- 24 GA CRCQ Steel, black electricallybonded epoxy finish
- Do not use for dryer venting



Broan-NuTone LLC Hartford, Wisconsin www.broan.com 800-558-1711

REFERENCE	QTY.	REMARKS	Project
			Location
			Architect
			Engineer
			Contractor
			Submitted by Date




Model 885AL

- For 3" or 4" round duct (4" to 3" transition included)
- Spring-loaded backdraft damper and bird screen
- .025 Aluminum natural finish
- Do not use for dryer venting

Model 610FA

- For 10" round duct
- .025 Aluminum natural
- Attachment collar 3-3/8" long
- Without backdraft damper
- Intended for make-up air inlet applications





Model 643

- For 8" round duct
- Built-in backdraft damper
- .025 Aluminum natural finish
- Attachment collar 3-3/8" long

Model 643FA


- Same features as Model 643
- Without backdraft damper
- Intended for make-up air inlet applications






Model 646

- For 6" round duct
- Polymeric construction white finish




Model 613

- For 12" round duct
- High capacity
- Built-in backdraft damper and bird screen
- .025 Aluminum natural finish




Model 441

- Gravity dampers
- Collar with bird screen for attaching 10" round duct
- 24 GA CRCQ steel construction with aluminum louvers




Model 450 Flexible Wall **Ducting Kit**

Includes 5 ft. of 4", flexible, vinyl ducting, 4" diameter metal duct connector, 2 duct clamps, 4" to 3" reducer and a polymeric louvered wall vent



Model WC650

- White wall cap for 4" round duct - includes 4 mounting screws
- Engineered resin material for impact and UV resistance
- Weighted backdraft damper guards against wind, birds or lint build-up
- 4" diameter metal duct connector



Model WVK2A Flexible Wall Ducting Kit

- Includes 5 ft. of 4", flexible, 2-ply metallic laminate ducting, 10" long 4" diameter metal duct, 2 duct clamps, 4" to 3" reducer, an engineered resin material wall vent, and mounting screws
- Duct conforms to UL181 Class 1 air connector requirements
- Do not use for dryer venting

