

SILK SBC LED LIGHTBAR ACCESSORIES



NEXUS® All-in-One LED Driver and Dimmer

NATL-SWEX100/24A 100W

NATL-SWEX/3FP 3 Face Plates

Voltage: 120V/24V
Wattage: 100W

Dimming: Integral Dimmer

Description: Eliminates the driver and allows 120V input and 12V output from a single gang box. 100-5% dimming and on/off switch.



Direct Plug-In LED Driver

NATL-524W 24W

NATL-545W 45W

NATL-596W 96W

Voltage: 120V/24V
Wattage: 24W, 45W or 96W
Dimming: Non-Dimmable
Cable Length: 6' (NATL-524 and 545) or 5' cord & plug and 44" power line connector (NATL-596)



Class II Hardwire LED Driver

NATL-5030HW 30W

NATL-5060HW 60W

NATL-5100HW 100W

Voltage: 120V/24V
Wattage: 30W, 60W or 100W
Dimming: Non-Dimmable
Includes: 10' Power Line Connector



Class II Hardwire LED Driver with Breakers, MLV Dimming

NATL-5096-24-HWD10 96W

Voltage: 120-277V/24V
Wattage: 96W
Dimming: 0-10V
Includes: 10' Power Line Connector



Class II Hardwire LED Driver with Breakers, MLV Dimming

NMT-303/24C2D1 3x100W

Voltage: 120V/24V
Wattage: (3) 100W
Dimming: Magnetic Low Voltage
Includes: (3) 10' Power Line Connectors



Class II Hardwire LED Driver with Regulator, MLV Dimming

NMTD-60/24D 60W

NMTD-96/24D 96W

Voltage: 120-277V/24V
Wattage: 60W or 96W

Dimming: Magnetic Low Voltage

Regulator: Integral regulator for constant current and voltage

Includes: 10' Power Line Connector



Power Line Connector

NATL-10 10'

NATL-30 30'

For use with Class II drivers. Carries output from driver, requires power line cable.



5" Power Line Splitter

NATL-302 B or W

Splits power line connector into two separate leads, requires power line cables. Available in Black or White.



In-Line Touch Dimmer

NATL-518W

72W max., no power fail memory, touch on/off and hold to dim.



DC Plug and Play Motion Sensor

NAL-856W

12' Max activation distance; 20 second auto off; 120° detection zone; Max Load 4A.



Low Voltage Splice Box

NATL-415W

Use to join low voltage lead to power line cable.



16AWG In-Wall Rated Wire

NATL-W16-2-250 16AWG 250'

NATL-W16-2-20 16AWG 20'

16 AWG low voltage Class II two-conductor, in-wall rated wire.



Terminal/Splitter Block

NATL-407 4-Way
2-3/8"L x 1-1/8"W x 7/8"D

NATL-408 8-Way
4"L x 1-1/8"W x 7/8"D

LED TAPE LIGHT ACCESSORIES & DRIVERS STANDARD / SIDE-LIT



Direct Plug-In LED Driver

NAPK-524/12 12V 24W
NATL-524W 24V 24W
NATL-545W 24V 45W

Input Voltage: 120V
Cable Length: 6 Feet



Direct Plug-In LED Driver

NAPK-550/12 12V 50W
NATL-596W 24V 96W

Input Voltage: 120V
Input Wire: 5' Cord and Plug
Output Wire: 44" Out Wire



Class II Hardwire LED Driver

NAPK-5030HW/12 12V 30W
NAPK-5060HW/12 12V 60W

NATL-5030HW 24V 30W
NATL-5060HW 24V 60W
NATL-5100HW 24V 100W

Input Voltage: 120-240V
Dimming: Non-Dimmable
Includes: 10' Power Line Connector



Class II Hardwire LED Driver
0-10V Dimming

NATL-5060-12-HWD10
12V 60W

NATL-5096-24-HWD10
24V 90W

Input Voltage: 120-277V
Dimming: 0-10V
Includes: 10' Power Line Connector



Class II Hardwire LED Driver
with Breakers, MLV Dimming

NMT-244/12C2D1
12V 4 x 60W

NMT-303/24C2D1
24V 3 x 100W

Input Voltage: 120V
Dimming: Magnetic Low Voltage
Includes: (3 or 4) 10' Power Line Connectors



Class II Hardwire LED Driver
with Regulator, MLV Dimming

NMTD-40/12D 12V 40W
NMTD-60/12D 12V 60W
NMTD-60/24D 24V 60W
NMTD-96/24D 24V 96W

Input Voltage: 120-277V
Dimming: Magnetic Low Voltage
Regulator: Integral regulator for constant current and voltage
Includes: 10' Power Line Connector



NEXUS® All-in-One LED
Driver and Dimmer

NATL-SWEX100/24A 24V 100W

NATL-SWEX60/12A 12V 60W

NATL-SWEX/3FP 3 Face Plates

Input Voltage: 120V
Dimming: Integral Dimmer
Description: Eliminates the driver and allows 120V input and 12V or 24V output from a single gang box. 100-5% dimming and on/off switch.



Power Line Connector

NALTL-10 10' Cable

NALTL-30 30' Cable

For use with Class II drivers. Carries output from driver, requires power line interconnectors.



5" Power Line Splitter

NATL-302 B or W

Splits power line connector into two separate leads, requires power line cable. Available in Black or White.



Touch Dimmer with Memory

NATL-518W

72W max., no power fail memory, touch on/off and hold to dim.



Low Voltage Splice Box

NATL-415W

Use to join low voltage lead to power line connector.



16AWG In-Wall Rated Wire

NATL-W16-2-250 16AWG 250'

NATL-W16-2-20 16AWG 20'

16 AWG low voltage Class II two-conductor, in-wall rated wire.



Terminal/Splitter Block

NATL-407 4-Way
2-3/8"L x 1-1/8"W x 7/8"D

NATL-408 8-Way
4"L x 1-1/8"W x 7/8"D

LED TAPE LIGHT ACCESSORIES AND DRIVERS HY-BRITE / HIGH OUTPUT



NEXUS® All-in-One LED Driver and Dimmer
NATL-SWEX100/24A 100W
NATL-SWEX/3FP 3 Face Plates
Voltage: 120V/24V
Wattage: 100W
Dimming: Integral Dimmer
Description: Eliminates the driver and allows 120V input and 12V output from a single gang box. 100-5% dimming and on/off switch.



Direct Plug-In LED Driver
NATL-524W 24W
NATL-545W 45W
NATL-596W 96W
Voltage: 120V/24V
Wattage: 24W, 45W or 96W
Dimming: Non-Dimmable
Cable Length: 6' (NATL-524 and 545) or 5' cord & plug and 44" power line connector (NATL-596)



Class II Hardwire LED Driver
NATL-5030HW 30W
NATL-5060HW 60W
NATL-5100HW 100W
Voltage: 120V/24V
Wattage: 30W, 60W or 100W
Dimming: Non-Dimmable
Includes: 10' Power Line Connector



Class II Hardwire LED Driver with Breakers, MLV Dimming
NATL-5096-24-HWD10 96W
Voltage: 120-277V/24V
Wattage: 96W
Dimming: 0-10V
Includes: 10' Power Line Connector



Class II Hardwire LED Driver with Breakers, MLV Dimming
NMT-303/24C2D1 3x100W
Voltage: 120V/24V
Wattage: (3) 100W
Dimming: Magnetic Low Voltage
Includes: (3) 10' Power Line Connectors



Class II Hardwire LED Driver with Regulator, MLV Dimming
NMTD-60/24D 60W
NMTD-96/24D 96W
Voltage: 120-277V/24V
Wattage: 60W or 96W
Dimming: Magnetic Low Voltage
Regulator: Integral regulator for constant current and voltage
Includes: 10' Power Line Connector



Power Line Connector
NATL-10 10' Cable
NATL-30 30' Cable
 For use with Class II drivers. Carries output from driver, requires power line cable.



5" Power Line Splitter
NATL-302 B or W
 Splits power line connector into two separate leads, requires power line cables. Available in Black or White.



In-Line Touch Dimmer
NATL-518W
 72W max., no power fail memory, touch on/off and hold to dim.



DC Plug and Play Motion Sensor
NAL-856W
 12' Max activation distance; 20 second auto off; 120° detection zone; Max Load 4A.



Low Voltage Splice Box
NATL-415W
 Use to join low voltage lead to power line connector.




16AWG In-Wall Rated Wire
NATL-W16-2-250 16AWG 250'
NATL-W16-2-20 16AWG 20'
 16 AWG low voltage Class II two-conductor, in-wall rated wire.



Terminal/Splitter Block
NATL-407 4-Way
 2-3/8"L x 1-1/8"W x 7/8"D
NATL-408 8-Way
 4"L x 1-1/8"W x 7/8"D

LED TAPE LIGHT ACCESSORIES AND DRIVERS RGB & CCT COLOR CHANGING



4' Aluminum Channel

NATHR-680

Used to mount tape light to various surfaces. Field cuttable.



4' Shallow Aluminum Channel

NATL-C23A with Wing
NATL-C24A

Used to mount tape light to various surfaces. Plastic diffuser and end caps included. Field cuttable.



4' Deep Aluminum Channels

NATL-C25A with Wing
NATL-C26A

Used to mount tape light to various surfaces. Plastic diffuser and end caps included. Field cuttable.



4' J-Style Aluminum Channels

NATL-C27A

Used to mount tape light to various surfaces. Field cuttable.



4' Corner Aluminum Channel

NATL-C28A

Plastic diffuser and End caps included. Field cuttable

Note: Dimming drivers are only for powering RGB and CCT tape. Do not use for dimming. Dimming is controlled by hand held remote and wall controls.



Direct Plug-In LED Driver

NAPK-524/12	12V 24W
NATL-524W	24V 24W
NATL-545W	24V 45W

Input Voltage: 120V
Cable Length: 6 Feet



Direct Plug-In LED Driver

NAPK-550/12	12V 50W
NATL-596W	24V 96W

Input Voltage: 120V
Input Wire: 5' Cord and Plug
Output Wire: 44" Out Wire



Class II Hardwire LED Driver

NAPK-5030HW/12	12V 30W
NAPK-5060HW/12	12V 60W

NATL-5030HW	24V 30W
NATL-5060HW	24V 60W
NATL-5100HW	24V 100W

Input Voltage: 120-240V
Dimming: Non-Dimmable
Includes: 10' Power Line Connector



Class II Hardwire LED Driver with Breakers

NMT-244/12C2D1	12V 4 x 60W
-----------------------	-------------

NMT-303/24C2D1	24V 3 x 100W
-----------------------	--------------

Input Voltage: 120V
Dimming: N/A for RGB/CCT tape
Includes: (3 or 4) 10' Power Line Connectors



Class II Hardwire LED Driver with Regulator

NMTD-40/12D	12V 40W
NMTD-60/12D	12V 60W

NMTD-60/24D	24V 60W
NMTD-96/24D	24V 96W

Input Voltage: 120-277V
Dimming: N/A for RGB/CCT tape
Regulator: Integral regulator for constant current and voltage
Includes: 10' Power Line Connector



Power Line Connector

NALTL-10	10' Cable
NALTL-30	30' Cable

For use with Class II drivers. Carries output from driver, requires power line interconnectors.



5' Power Line Splitter

NATL-302	B or W
-----------------	--------

Splits power line connector into two separate leads, requires power line cable. Available in Black or White.



16AWG In-Wall Rated Wire

NATL-W16-2-250	16AWG 250'
NATL-W16-2-20	16AWG 20'

16 AWG low voltage Class II two-conductor, in-wall rated wire.



Low Voltage Splice Box

NATL-415W

Joins low voltage lead to low voltage power line connector or interconnector.



Terminal/Splitter Block

NATL-407	4-Way 2-3/8"L x 1-1/8"W x 7/8"D
-----------------	------------------------------------

NATL-408	8-Way 4"L x 1-1/8"W x 7/8"D
-----------------	--------------------------------

LED TAPE LIGHT ACCESSORIES AND DRIVERS RGBW COLOR CHANGING



Direct Plug-In LED Driver

NATL-524W	24W
NATL-545W	45W

Voltage: 120V/24V
Wattage: 24W, 45W or 96W
Dimming: Non-Dimmable
Cable Length: 6'



Direct Plug-In LED Driver

NATL-596W	96W
------------------	-----

Voltage: 120V/24V
Wattage: 96W
Dimming: Non-Dimmable
Input Wire: 5' Cord and Plug
Output Wire: 44" Out Wire



Class II Hardwire LED Driver

NATL-5030HW	30W
NATL-5060HW	60W
NATL-5100HW	100W

Voltage: 120V/24V
Wattage: 30W, 60W or 100W
Dimming: Non-Dimmable
Includes: 10' Power Line Connector



Class II Hardwire LED Driver with Breakers

NMT-303/24C2D1	3x100W
-----------------------	--------

Voltage: 120V/24V
Wattage: (3) 100W
Dimming: N/A for RGBW tape
Includes: (3) 10' Power Line Connectors



Class II Hardwire LED Driver with Regulator

NMTD-60/24D	60W
NMTD-96/24D	96W

Voltage: 120-277V/24V
Wattage: 60W or 96W
Dimming: N/A for RGBW tape
Regulator: Integral regulator for constant current and voltage
Includes: 10' Power Line Connector



Power Line Connector

NATL-10	10' Cable
NATL-30	30' Cable

For use with Class II drivers. Carries output from driver, requires power line cable.



5" Power Line Splitter

NATL-302	B or W
-----------------	--------

Splits power line connector into two separate leads, requires power line interconnector. Available in Black or White.



Low Voltage Splice Box

NATL-415W	
------------------	--

Use to join low voltage lead to power line connector.



16AWG In-Wall Rated Wire

NATL-W16-2-250	16AWG 250'
NATL-W16-2-20	16AWG 20'

16 AWG low voltage Class II two-conductor, in-wall rated wire.



Terminal/Splitter Block

NATL-407	4-Way 2-3/8"L x 1-1/8"W x 7/8"D
NATL-408	8-Way 4"L x 1-1/8"W x 7/8"D

NOTE:

Each RGBW Tape Light run requires a driver, controller, power line interconnector and tape. To accomplish the RGBW color changing, you must use the RGBW controller between the Driver and the RGBW tape.



LED TAPE LIGHT ACCESSORIES AND DRIVERS CONTINUOUS WHITE TAPE LIGHT



NEXUS® All-in-One LED Driver and Dimmer

NATL-SWEX100/24A 100W

NATL-SWEX/3FP 3 Face Plates

Voltage: 120V/24V
Wattage: 100W
Dimming: Integral Dimmer
Description: Eliminates the driver and allows 120V input and 12V output from a single gang box. 100-5% dimming and on/off switch.



Direct Plug-In LED Driver

NATL-524W 24W

NATL-545W 45W

NATL-596W 96W

Voltage: 120V/24V
Wattage: 24W, 45W or 96W
Dimming: Non-Dimmable
Cable Length: 6' (NATL-524 and 545) or 5' cord & plug and 44" power line connector (NATL-596)



Class II Hardwire LED Driver

NATL-5030HW 30W

NATL-5060HW 60W

NATL-5100HW 100W

Voltage: 120V/24V
Wattage: 30W, 60W or 100W
Dimming: Non-Dimmable
Includes: 10' Power Line Connector



Class II Hardwire LED Driver with Breakers, MLV Dimming

NATL-5096-24-HWD10 96W

Voltage: 120-277V/24V
Wattage: 96W
Dimming: 0-10V
Includes: 10' Power Line Connector



Class II Hardwire LED Driver with Breakers, MLV Dimming

NMT-303/24C2D1 3x100W

Voltage: 120V/24V
Wattage: (3) 100W
Dimming: Magnetic Low Voltage
Includes: (3) 10' Power Line Connectors



Class II Hardwire LED Driver with Regulator, MLV Dimming

NMTD-60/24D 60W

NMTD-96/24D 96W

Voltage: 120-277V/24V
Wattage: 60W or 96W
Dimming: Magnetic Low Voltage
Regulator: Integral regulator for constant current and voltage
Includes: 10' Power Line Connector



Power Line Connector

NATL-10 10' Cable

NATL-30 30' Cable

For use with Class II drivers. Carries output from driver, requires power line cable.



5" Power Line Splitter

NATL-302 B or W

Splits power line connector into two separate leads, requires power line cables. Available in Black or White.



In-Line Touch Dimmer

NATL-518W

72W max., no power fail memory, touch on/off and hold to dim.



DC Plug and Play Motion Sensor

NAL-856W

12" Max activation distance; 20 second auto off; 120° detection zone; Max Load 4A.



Low Voltage Splice Box

NATL-415W

Use to join low voltage lead to power line connector.



16AWG In-Wall Rated Wire

NATL-W16-2-250 16AWG 250'

NATL-W16-2-20 16AWG 20'

16 AWG low voltage Class II two-conductor, in-wall rated wire.



Terminal/Splitter Block

NATL-407 4-Way
2-3/8"L x 1-1/8"W x 7/8"D

NATL-408 8-Way
4"L x 1-1/8"W x 7/8"D

ACCENT, UNDER CABINET, LINEAR, COVE **JOSH LED PUCK LIGHTS**

ACCESSORIES AND DRIVERS **12V LED PUCK LIGHT**



6-Port Power Line Interconnect

NMPA-6P-24B Black
NMPA-6P-24W White

Terminal block connects up to six LED Josh Puck lights to a Nora driver. Includes 24" cord with RCA jack.



Extension Cable

NMPA-EW-12 12" Cable
NMPA-EW-24 24" Cable
NMPA-EW-36 36" Cable
NMPA-EW-48 48" Cable

Finish: Black (B), White (W)
Used to extend the length of the cable from the puck to the terminal block. Linkable up to 110".



2' Wire Raceway

NATL-422 B or W

Field-cutttable plastic. Includes wire channel with double faced tape and cover. Black or White.



in-Line Touch Dimmer

NATL-518W

72W max., no power fail memory, touch on/off and hold to dim.



DC Plug and Play Motion Sensor

NAL-856W

12' Max activation distance; 20 second auto off; 120° detection zone; Max Load 4A.



NEXUS® All-in-One LED Driver and Dimmer

NATL-SWEX60/12A 60W

NATL-SWEX/3FP3 Face Plates

Voltage: 120V/12V

Dimming: Integral Dimmer

Description: Eliminates the driver and allows 120V input and 12V output from a single gang box. 100-5% dimming and on/off switch.



Direct Plug-In LED Driver

NAPK-524/12 24W

NAPK-550/12 50W

Voltage: 120V/12V

Wattage: 24W or 50W

Dimming: Non-Dimmable

Cable Length:

6' cord & plug and 60" power line connector for NAPK-550/12



Class II Hardwire LED Driver

NAPK-5030HW/12 30W

NAPK-5060HW/12 60W

Voltage: 120-240V/12V

Wattage: 30W or 60W

Dimming: Non-Dimmable

Includes: 10' Power Line Connector



Class II Hardwire LED Driver with Breakers, MLV Dimming

NMT-244/12C2D1 4x60W

Voltage: 120V/12V

Wattage: (4) 60W

Dimming: Magnetic Low Voltage

Includes: (4) 10' Power Line Connectors



Class II Hardwire LED Driver 0-10V Dimming

NATL-5060-12-HWD10 60W

Voltage: 120-277V/12V

Wattage: 60W

Dimming: 0-10V

Includes: 10' Power Line Connector



Class II Hardwire LED Driver with Regulator, MLV Dimming

NMTD-40/12D 40W

NMTD-60/12D 60W

Voltage: 120-277V/12V

Wattage: 40W or 60W

Dimming: Magnetic Low Voltage

Regulator: Integral regulator for constant current and voltage

Includes: 10' Power Line Connector



Power Line Connector

NATL-10 10' Cable

NATL-30 30' Cable

For use with Class II drivers.

Carries output from driver, requires power line cable.



Power Line Splitter

NATL-302 5" Cable

Splits power line connector into two separate leads, requires power line interconnects. Available in black or white.



Low Voltage Splice Box

NATL-415W

Use to join low voltage lead to low voltage power line connector or interconnector.



16AWG In-Wall Rated Wire

NATL-W16-2-250 16AWG 250'

NATL-W16-2-20 16AWG 20'

16 AWG low voltage Class II two-conductor, in-wall rated wire.

LED PUCK LIGHTS ACCENT, UNDER CABINET, LINEAR, COVE LIGHTING

12V LED PUCK LIGHT ACCESSORIES AND DRIVERS



Splitter

NAPK-701B	Black
NAPK-701W	White

To separate 4 puck light runs from a single driver or to split a run between puck lights. One in and four out.



Interconnection Cable

NAPK-702	2" Cable
NAPK-703	3" Cable
NAPK-706	6" Cable
NAPK-712	12" Cable
NAPK-724	24" Cable
NAPK-736	36" Cable
NAPK-748	48" Cable

Finish: Black (B), White (W)
Allows easy linking of two pucks.



Mini Coupler

NAPK-713B	Black
NAPK-713W	White

Used to connect two interconnection cables together or to add interconnection cable to power line interconnector.
Dim.: 3/8" W; 3/4" L; 1/4" H



12" Power Line Interconnector with Switch

NAPK-711B	Black
NAPK-711W	White

Allows individual switching of any LED Puck Light run.



18" Power Line Interconnector

NAPK-709B	Black
NAPK-709W	White

Connects puck light to a driver.



Recessed Housing Accessory

NMPKA-RECBZ	Bronze
NMPKA-RECC	Chrome
NMPKA-RECW	White

Used to mount puck light recessed and flush



2' Wire Raceway

NATL-422	B or W
-----------------	--------

Field-cutttable plastic. Includes wire channel with double faced tape and cover. Black or White.



Power Line Connector

NATL-10	10' Cable
NATL-30	30' Cable

Carries output from driver, requires power line interconnector. For use with Class II drivers.



Low Voltage Splice Box

NATL-415W	
------------------	--

Use to join low voltage lead to low voltage power line connector or interconnector.



NEXUS® All-in-One LED Driver and Dimmer

NATL-SWEX60/12A	60W
------------------------	-----

NATL-SWEX/3FP3 Face Plates

Voltage: 120V/12V
Dimming: Integral Dimmer
Description: Eliminates the driver and allows 120V input and 12V output from a single gang box. 100-5% dimming and on/off switch.



Direct Plug-In LED Driver

NAPK-524/12	24W
NAPK-550/12	50W

Voltage: 120V/12V
Wattage: 24W or 50W
Dimming: Non-Dimmable
Cable Length: 6' cord & plug and 60" power line connector for NAPK-550/12



Class II Hardwire LED Driver

NAPK-5030HW/12	30W
NAPK-5060HW/12	60W

Voltage: 120-240V/12V
Wattage: 30W or 60W
Dimming: Non-Dimmable
Includes: 10' Power Line Connector



Class II Hardwire LED Driver with Breakers, MLV Dimming

NMT-244/12C2D1	4x60W
-----------------------	-------

Voltage: 120V/12V
Wattage: (4) 60W
Dimming: Magnetic Low Voltage
Includes: (4) 10' Power Line Connectors



Class II Hardwire LED Driver 0-10V Dimming

NATL-5060-12-HWD10	60W
---------------------------	-----

Voltage: 120-277V/12V
Wattage: 60W
Dimming: 0-10V
Includes: 10' Power Line Connector



Class II Hardwire LED Driver with Regulator, MLV Dimming

NMTD-40/12D	40W
NMTD-60/12D	60W

Voltage: 120-277V/12V
Wattage: 40W or 60W
Dimming: Magnetic Low Voltage
Regulator: Integral regulator for constant current and voltage
Includes: 10' Power Line Connector