



STRAIGHT BLADE RECEPTACLES

Hard Use Specification Grade Receptacles 15A & 20A, 125 & 125/250V



5262I




5362GN

Features

- Corrosion-resistant, plated and tabbed steel strap is locked in to face and back body to resist pulling away from face/body assembly.
- .032 inch thick, brass, triple-wipe power contacts for lasting retention.
- Easily accessed break-off, line-contact connecting tab for fast, easy split-circuit wiring.
- Impact-resistant nylon face.
- 8 hole internal screw-pressure-plate back wire terminals accept #10 – 14 AWG solid or stranded copper or copper-clad conductors.
- Terminal compartments isolated from each other for positive conductor containment.
- Tri-drive terminal and mounting screws.
- Auto-ground clip assures positive ground.

CATALOG NUMBER	RATING		COLOR	NEMA CONFIG. NO.	3rd PARTY COMPLIANCE		
	A.	V.			UL498	FSUL WC596	C22.2 No. 42
DUPLIX RECEPTACLES BACK & SIDE WIRE							
5262I	15	125	Ivory	5-15R	•	•	•
5262W	15	125	White	5-15R	•	•	•
5262	15	125	Brown	5-15R	•	•	•
5262GRY	15	125	Gray	5-15R	•	•	•
5262BK	15	125	Black	5-15R	•	•	•
5262RED	15	125	Red	5-15Ra	•	•	•
5262LA	15	125	Light Almond	5-15R	•	•	•
5262BL	15	125	Blue	5-15R	•	•	•
5362I	20	125	Ivory	5-20R	•	•	•
5362W	20	125	White	5-20R	•	•	•
5362	20	125	Brown	5-20R	•	•	•
5362GRY	20	125	Gray	5-20R	•	•	•
5362BK	20	125	Black	5-20R	•	•	•
5362RED	20	125	Red	5-20R	•	•	•
5362LA	20	125	Light Almond	5-20R	•	•	•
5362BL	20	125	Blue	5-20R	•	•	•
5362GN	20	125	Green	5-20R	•	•	•
5362OR	20	125	Orange	5-20R	•	•	•
COMBINATION DUPLIX RECEPTACLES SIDE WIRE							
5290I	15	125/250	Ivory	5/6-15R	•	•	•
5290	15	125/250	Brown	5/6-15R	•	•	•
5890I	20	125/250	Ivory	5/6-20R	•	•	•
5890W	20	125/250	White	5/6-20R	•	•	•
5890	20	125/250	Brown	5/6-20R	•	•	•



For Bulk Packaging Solutions consult factory.

All devices listed on this page conform to NEMA WD-1 and WD-6.

TECHNICAL SPECIFICATIONS

Hard Use Specification Grade Receptacles


Back & Side Wire 2 Pole, 3 Wire Grounding 15 & 20A, 125 & 250V

Typical Specifications



Manufacturer's Identification: Pass & Seymour® 5262
 Description: Straight Blade Duplex Receptacle – Hard Use Specification Grade
 Type: 2 Pole, 3 Wire Grounding
 Rating: 15A, 125V
 3rd Party Compliance: UL Listed, File Number E140596, Standard UL498, Federal Specification WC596. CSA Certified, File Number LR16063, Standard CSA-C22.2 No. 42.27. Conforms to NEMA WD-1 and WD-6.

CATALOG NUMBER	COLOR	RATING	NEMA CONFIG. NO.	CATALOG NUMBER	COLOR	RATING	NEMA CONFIG. NO.
<input type="checkbox"/> 5262I	Ivory	15A 125V	5-15R	<input type="checkbox"/> 5362BK	Black	20A 125V	5-20R
<input type="checkbox"/> 5262W	White	15A 125V	5-15R	<input type="checkbox"/> 5362RED	Red	20A 125V	5-20R
<input type="checkbox"/> 5262	Brown	15A 125V	5-15R	<input type="checkbox"/> 5362LA	Lt. Almond	20A 125V	5-20R
<input type="checkbox"/> 5262GRY	Gray	15A 125V	5-15R	<input type="checkbox"/> 5362BL	Blue	20A 125V	5-20R
<input type="checkbox"/> 5262BK	Black	15A 125V	5-15R	<input type="checkbox"/> 5362GN	Green	20A 125V	5-20R
<input type="checkbox"/> 5262RED	Red	15A 125V	5-15R	<input type="checkbox"/> 5362OR	Orange	20A 125V	5-20R
<input type="checkbox"/> 5262LA	Lt. Almond	15A 125V	5-15R	<input type="checkbox"/> 5290I*	Ivory	15A 125/250V	5/6-15R
<input type="checkbox"/> 5262BL	Blue	15A 125V	5-15R	<input type="checkbox"/> 5290*	Brown	15A 125/250V	5/6-15R
<input type="checkbox"/> 5362I	Ivory	20A 125V	5-20R	<input type="checkbox"/> 5890I*	Ivory	20A 125/250V	5/6-20R
<input type="checkbox"/> 5362W	White	20A 125V	5-20R	<input type="checkbox"/> 5890W*	Wwhite	20A 125/250V	5/6-20R
<input type="checkbox"/> 5362	Brown	20A 125V	5-20R	<input type="checkbox"/> 5890*	Brown	20A 125/250V	5/6-20R
<input type="checkbox"/> 5362GRY	Gray	20A 125V	5-20R				

*Side wire only.



15 & 20 Amp



Performance

Electrical

Dielectric Voltage: Withstands 2000V minimum
 Maximum Working Voltage: 250V
 Current Interrupting: Certified for current interrupting at full-rated current
 Temperature Rise: Max 30°C temperature rise at full-rated current after 50 cycles of overload at 150% of rated current with direct current

Mechanical

Terminal Identification: Terminal Identification in accordance with UL498 (Brass, White, Green)
 Terminal Accommodation: #14 – #10 AWG copper conductor only
 Product Identification: Ratings are a permanent part of the device

Environmental

Flammability: UL94 V2
 Operating Temperature: Maximum continuous +60°C, minimum -40°C (without impact)

Materials

Face: Nylon
 Back Body: PVC
 Contacts: .032" (.8) Brass
 Clamping Plate: .080" Steel
 Mounting Strap: .042" Steel
 Terminal Screws: Tri-Drive Brass
 Hex Head
 Grounding Screw: Tri-Drive Zinc-Plated Steel
 Assembly Rivets: Steel
 Auto-Ground Clip: Stainless Steel
 Mounting Screws: Tri-Drive Steel

Consult Straight Blade Section B for complete compliance listing.

Project
Location/Type