



# INDUSTRIAL SPEC GRADE TURNLOK® LOCKING DEVICES

15 Amp NEMA L515 2 Pole, 3 Wire 15A, 125V




4710




4700




15A Connector




4715SS



4792



15A Plug



4716SS

CATALOG NUMBER	RATING		DESCRIPTION/COLOR	CORD DIAMETER	NEMA CONFIG. NO.	3rd PARTY COMPLIANCE		
	A.	V.				UL498	FSUL WC596	CSA
<b>RECEPTACLES</b>								
4710	15	125	Single Receptacle		L5-15R	•		•
IG4710	15	125	Single Receptacle, Orange, Isolated Ground		L5-15R	•		•
4700	15	125	Duplex Receptacle		L5-15R	•		•
IG4700	15	125	Duplex Receptacle, Orange, Isolated Ground		L5-15R	•		•
4792	15	125	Combination Straight Blade and Locking		5-15R and L5-15R	•		
<b>CONNECTORS IP20 SUITABILITY</b>								
PSL515C	15	125	Black Back, White Front Body	.230"-.720"	L5-15R	•	•	•
CRL515C	15	125	Yellow Back, White Front Body, Corrosion-Resistant	.230"-.720"	L5-15R	•	•	•
<b>PLUGS IP20 SUITABILITY</b>								
PSL515P	15	125	Black Back, White Front Body	.230"-.720"	L5-15P	•	•	•
CRL515P	15	125	Yellow Back, White Front Body, Corrosion-Resistant	.230"-.720"	L5-15P	•	•	•
<b>FLANGED INLETS &amp; OUTLETS</b>								
4716SS	15	125	Gray Inlet		L5-15P	•		•
4715SS	15	125	Gray Outlet		L5-15R	•		•
<b>STRAIGHT BLADE/LOCKING ADAPTERS</b>								
44859	15	125	High-Visibility Yellow		5-15R/L5-15P			



NEMA L5-15P



NEMA L5-15R




NEMA 5-15R

Reference Pages G-38 and G-39 for Accessories.


All devices listed on this page conform to NEMA WD-1 and WD-6.

# TECHNICAL SPECIFICATIONS


## 15A Turnlok® Receptacles




4710




4700



4792



4550



4750

### Typical Specifications

Manufacturer's Identification: Pass & Seymour® 4700

Description: Locking Receptacle, Power Supply

Type: 2 Pole, 3 Wire Grounding

Rating: 15A, 125V

Configuration: NEMA L5-15R

3rd Party Compliance: UL Listed, File Number E146159, Standard UL498, Attachment Plugs and Receptacles. Federal Specification WC596. CSA Certified, File Number LR1765, Standard CSA-C22.2 No. 42, General Use Receptacles and Attachment Plugs. Conforms to NEMA WD-1 and WD-6.

AMPS	CATALOG NUMBER	NEMA CONFIG. NO.	AMPS	CATALOG NUMBER	NEMA CONFIG. NO.
15	☐ 4710	L5-15R	15	☐ 4550	L6-15R
15	☐ 4700	L5-15R	15	☐ 4760	L7-15R
15	☐ 4792	L5-15R	15	☐ 4750	L7-15R
15	☐ 4560	L5-15R			

### Performance

#### Electrical

Dielectric Withstand Voltage: 2000V minimum

Maximum Working Voltage: 600VAC

Current Interrupting: Certified for current interrupting at full-rated current

Temperature Rise: 30°C max. after 50 cycles at 150% rated current

#### Mechanical

Terminal Accommodation: #18 AWG min. – #10 AWG max.

Product Identification: Amperage, Voltage, NEMA Configuration molded into face

#### Environmental

Flammability: UL94 V2

Operating Temperature: Maximum continuous +75°C, minimum -40°C without impact

### Materials

Front Body: Nylon

Back Body: Nylon


Mounting Strap: Steel

Contacts: Brass


Terminal Clamps: Brass

Terminal Screws: Brass

Mounting Screws: Zinc-Plated Steel



4760



4560



NEMA L5-15R



NEMA L6-15R



NEMA L7-15R

Consult Turnlok® Section G for complete compliance listing.

<b>Project</b>
<b>Location/Type</b>