



# INDUSTRIAL SPEC GRADE TURNLOK® LOCKING DEVICES


15 Amp NEMA L615 & L715 2 Pole, 3 Wire 15A, 250 & 277V




4560




4550




4760




4750



15A Connector



15A Plug



15 Amp Angle Plug

CATALOG NUMBER	RATING		DESCRIPTION/COLOR	CORD DIAMETER	NEMA CONFIG. NO.	3rd PARTY COMPLIANCE		
	A.	V.				UL498	FSUL WC596	CSA
<b>RECEPTACLES</b>								
4560	15	250	Single Receptacle		L6-15R	•		
4550*	15	250	Duplex Receptacle		L6-15R	•		
4760	15	277	Single Receptacle		L7-15R	•		•
IG4760	15	277	Single Receptacle, Orange, Isolated Ground		L7-15R	•		•
4750	15	277	Duplex Receptacle		L7-15R	•		•
<b>CONNECTORS IP20 SUITABILITY</b>								
PSL615C	15	250	Black Back, White Front Body	.230"-.720"	L6-15R	•	•	•
PSL715C	15	277	Black Back, White Front Body	.230"-.720"	L7-15R	•	•	•
<b>PLUGS IP20 SUITABILITY</b>								
PSL615P	15	250	Black Back, White Front Body	.230"-.720"	L6-15P	•	•	•
PSL615PAN	15	250	Angled Plug, Black Back, White Front Body	.320"-.655"	L6-15P	•		
PSL715P	15	277	Black Back, White Front Body	.230"-.720"	L7-15P	•	•	•
PSL715PAN	15	277	Angled Plug, Black Back, White Front Body	.320"-.655"	L7-15P	•		
<b>PLUGS IP20 SUITABILITY</b>								
614	15	250	Gray Outlet		L6-15R			
L0714	15	277	Gray Outlet		L7-15R			



NEMA L6-15P



NEMA L6-15R



NEMA L7-15P




NEMA L7-15R


\*Not designed for split circuits. Reference Pages G-38 and G-39 for Accessories.

# TECHNICAL SPECIFICATIONS


## 15A Turnlok® Receptacles




**4710**




**4700**



**4792**



**4550**



**4750**

### Typical Specifications

Manufacturer's Identification: Pass & Seymour® 4700

Description: Locking Receptacle, Power Supply


Type: 2 Pole, 3 Wire Grounding

Rating: 15A, 125V


Configuration: NEMA L5-15R

3rd Party Compliance: UL Listed, File Number E146159, Standard UL498, Attachment Plugs and Receptacles. Federal Specification WC596. CSA Certified, File Number LR1765, Standard CSA-C22.2 No. 42, General Use Receptacles and Attachment Plugs. Conforms to NEMA WD-1 and WD-6.

AMPS	CATALOG NUMBER	NEMA CONFIG. NO.	AMPS	CATALOG NUMBER	NEMA CONFIG. NO.
15	☐ 4710	L5-15R	15	☐ 4550	L6-15R
15	☐ 4700	L5-15R	15	☐ 4760	L7-15R
15	☐ 4792	L5-15R	15	☐ 4750	L7-15R
15	☐ 4560	L5-15R			



**4760**



**4560**



**NEMA L5-15R**



**NEMA L6-15R**



**NEMA L7-15R**

### Performance

#### Electrical

Dielectric Withstand Voltage: 2000V minimum

Maximum Working Voltage: 600VAC

Current Interrupting: Certified for current interrupting at full-rated current

Temperature Rise: 30°C max. after 50 cycles at 150% rated current

#### Mechanical

Terminal Accommodation: #18 AWG min. – #10 AWG max.

Product Identification: Amperage, Voltage, NEMA Configuration molded into face

#### Environmental

Flammability: UL94 V2

Operating Temperature: Maximum continuous +75°C, minimum -40°C without impact

### Materials

Front Body: Nylon

Back Body: Nylon

Mounting Strap: Steel

Contacts: Brass

Terminal Clamps: Brass

Terminal Screws: Brass

Mounting Screws: Zinc-Plated Steel

Consult Turnlok® Section G for complete compliance listing.

<b>Project</b>
<b>Location/Type</b>