## SLATER<sup>®</sup> PLASTIC BOXES

## 4" Round Ceiling Boxes With Dual Threaded Mounting Holes



S120RAC



S120RGAC



S120JAC



S120JGAC







	CU. IN.			NSIONS N.)	WIRES (AWG)	QTY. PER Carton	UL LISTED MAX. WEIGHT RATING
CATALOG NUMBER	VOL.	DESCRIPTION	DIA.	DEPTH			FIXTURE
CEILING BOXES							
S120RAC	20.25	4" round. 2 captive mounting nails. 4 Auto/Clamps.	4	23/16	10 No. 14 9 No. 12 8 No. 10	50	50 lbs.
S120RGAC	20.25	4" round with ground lug. 2 captive mounting nails. 4 Auto/Clamps.	4	23/16	10 No. 14 9 No. 12 8 No. 10	50	50 lbs.
S120JAC	20.25	4" round. J-bracket with 2 captive mounting nails. 4 Auto/Clamps.	4	23/16	10 No. 14 9 No. 12 8 No. 10	50	50 lbs.
S120JGAC	20.25	4" round with ground lug. J-bracket with 2 captive mounting nails. 4 Auto/Clamps.	4	23/16	10 No. 14 9 No. 12 8 No. 10	50	50 lbs.
S120HAC	20.25	4" round. Bar-hanger adjusts to 16" or 24" joist spacing. 4 Auto/Clamps.	4	23/16	10 No. 14 9 No. 12 8 No. 10	50	50 lbs.
S120HGAC	20.25	4" round with ground lug. Bar-hanger adjusts to 16" or 24" joist spacing. 4 Auto/Clamps.	4	23/16	10 No. 14 9 No. 12 8 No. 10	50	50 lbs.
S120RACS	20.25	4" round. 2 captive mounting screws. 4 Auto/Clamps.	4	2 <sup>3</sup> / <sub>16</sub>	10 No. 14 9 No. 12 8 No. 10	50	50 lbs.

All boxes are UL listed. UL Classified for 2 Hour Fire Resistance. Dual mounting accommodates both 2.75" and 3.5" fixtures.

CATALOG NUMBER	DESCRIPTION	QTY. PER CARTON					
COVERS FOR 4" ROUND BOXES							
4RBC	4" round flat blank cover – gray	50					
4RBCW	4" round flat blank cover – white	50					



4RBC