

# SLATER® PLASTIC BOXES

Switch & Outlet Boxes with Captive Mounting Nails on Each End



P118R



P1-18-RN




P1-22-R




P122RN



P1-22-N



PH1-22-R



P1-22-C



P2-35-RAC



P2-35-RACMH



P354RACMH

CATALOG NUMBER	CU. IN. VOL.	DESCRIPTION	DIMENSIONS			WIRE FILL (AWG)	QTY. PER CARTON
			L	W	D		
<b>SWITCH &amp; OUTLET BOXES WITH THREADED MOUNTING HOLES</b>							
P118R	18.0	Single gang. 2 Quick/Entries® each end.	3¾	2¼	2 <sup>23</sup> / <sub>32</sub>	9 No. 14 8 No. 12 7 No. 10	100
P118RN	18.0	Single gang. Reverse angled captive mounting nail. 2 Quick/Entries® each end. Used for manufactured housing.	3¾	2¼	2 <sup>23</sup> / <sub>32</sub>	9 No. 14 8 No. 12 7 No. 10	100
P122C	22.0	Single gang. With EZ Grip – a temporary hold feature.	3¾	2¼	4	11 No. 14 10 No. 12 9 No. 10	100
PH122R	22.0	Single gang. Horizontal. Captive mounting nail each side.	3¾	2¼	3 <sup>7</sup> / <sub>8</sub>	11 No. 14 10 No. 12 9 No. 10	100
P235RAC	35.0	Two gang. 4 Auto/Clamps® each end.	3 <sup>31</sup> / <sub>32</sub>	3 <sup>31</sup> / <sub>32</sub>	3 <sup>3</sup> / <sub>8</sub>	17 No. 14 15 No. 12 14 No. 10	100
P235RACMH	35.0	Two gang. 4 Auto/Clamps® each end. 3" depth for manufactured housing walls.	3 <sup>31</sup> / <sub>32</sub>	3 <sup>31</sup> / <sub>32</sub>	3	17 No. 14 15 No. 12 14 No. 10	100
P354RACMH	54.0	Three gang. 6 Auto/Clamps® each end. 3 <sup>1</sup> / <sub>16</sub> " depth for manufactured housing walls.	3 <sup>13</sup> / <sub>16</sub>	5 <sup>15</sup> / <sub>16</sub>	3 <sup>1</sup> / <sub>16</sub>	27 No. 14 24 No. 12 21 No. 10	50
<b>DEEP SWITCH &amp; OUTLET BOXES WITH THREADED MOUNTING HOLES</b>							
P122R	22.5	Single gang deep. 2 Quick/Entries® each end. Extra deep for dimmers, GFCIs and thermostats, yet suitable for 2 x 4 construction.	3¾	2¼	3 <sup>3</sup> / <sub>8</sub>	11 No. 14 10 No. 12 9 No. 10	100
P122RN	22.5	Single gang deep. Reverse angled captive mounting nail. 2 Quick/Entries® each end. Extra deep for dimmers, GFCIs and thermostats, yet suitable for 2 x 4 construction.	3¾	2¼	3 <sup>3</sup> / <sub>8</sub>	11 No. 14 10 No. 12 9 No. 10	100
P122N	22.5	Single gang deep. Vertical bracket mount.	3¾	2¼	3 <sup>3</sup> / <sub>8</sub>	11 No. 14 10 No. 12 9 No. 10	100

All boxes are UL Listed.  
UL Classified for 2 Hour Fire Resistance (Does not apply to P122N.)