

WALL PLATES & SPECIALTIES

Incandescent Lampholders, Neon Pilot Lights & Panelites

Incandescent Lampholders




Designed to give adequate light when installed behind a louvre plate or indicator jewel. Mounts in standard wall box. Plate mounting is 2-3/8" and 3-13/16". UL listed for 120 VAC circuits. Plate not included.

Description **Catalog Number**
Standard lampholder, 4 Watt **2152**

Extra long life: Integral series resistor in base reduces light output by about 40%, but increases lamp life more than ten times. Plate not included.

Extra long life, 4 Watt **2156**




Application

Lampholders and louver plates are an ideal combination for providing bright, shielded light in hallways and pathways. They increase safety in corridors, theater aisles, porches, stairways, etc. A wide choice of plates gives unlimited possibilities for designing the perfect night light installation. Available in brushed brass, custom-painted stainless steel and stainless steel.

For the complete listing of Louver Plates, see Page P-22 .

Energy Efficient Gasket



Description **Catalog Number**
Gangable gasket, use for toggle, duplex, GFCI or blank..... **GASKET1**

Neon Pilot Lights




Long life neon bulb emits indicating light through transparent lens to show power is on. May be installed at the load, at switching posts or at remote locations. We suggest the wall plate be engraved to explain indication. Fits standard wall box and takes standard toggle switch plate opening. Plate mounting is 2-3/8". UL listed 120/277 VAC.

Description **Catalog Number**
With green lens **2151GN**
With red lens **2151RED**
With white lens **2151W**

Panelites



2220PL



2200PL



2219PL

Panelites are attractive wall plates that light the message "IN USE" to protect darkrooms, private meeting areas, etc. Also available with a clear face for user to apply his own message. Furnished complete ready to wire. Panelites may be installed in a feed-through wall box, with the Panelite on one wall and a pilot light on the other. Panelite also may be installed in a standard wall box with the control switch in any desired location. With 4 Watt Incandescent bulb. Ivory plate.

Description **Catalog Number**
IN USE, for Horizontal mounting **2219PL**
IN USE, for Vertical mounting **2220PL**
With clear unprinted face **2200PL**

UL Listed and CSA Certified.